

AD 654034

ABSTRACTS OF RESEARCH AND DEVELOPMENT DOCUMENTS

Vol. 20, No. 7, 1st - 15th April, 1967

Introduction

1. R & D Abstracts is issued twice a month by Technical Information and Library Services, Ministry of Technology. It is intended primarily to serve Ministry of Technology branches and their contractors by abstracting, as promptly as possible classified and unclassified reports which are received from the Ministry, other government agencies, industry and universities.
2. The reports which are listed in R & D Abstracts are catalogued in TIL by author, originator, report number, title, subject (Universal Decimal Classification) and contract and project numbers.
3. The suffix CVD shown after the TIL reference number of certain items indicates that the report in question was selected by the Department of Naval Physical Research (CVD) (Ministry of Defence) representative in Washington, or is issued in connection with CVD-sponsored work.
4. Requests for reports, quoting the TIL Reference Number given at the top left of each item, should be addressed to:-

The Secretary,  
Ministry of Technology,  
TIL, Block A,  
Station Square House,  
St. Mary Cray,  
Orpington, Kent.

5. The circulation of some of the reports listed is subject to special restrictions. Requesters of such reports may have to provide a need to know before the documents can be supplied to them.

6. Enquiries on editorial matters only (not requests for reports, see (4) above), should be addressed to:-

The Secretary,  
Ministry of Technology,  
TIL H, Room 508,  
Block A,  
Station Square House,  
St. Mary Cray,  
Orpington, Kent.

ABSTRACTS OF RESEARCH AND DEVELOPMENT DOCUMENTS

Vol. 20, No. 7, 1st - 15th April, 1967

Introduction

1. R & D Abstracts is issued twice a month by Technical Information and Library Services, Ministry of Technology. It is intended primarily to serve Ministry of Technology branches and their contractors by abstracting, as promptly as possible classified and unclassified reports which are received from the Ministry, other government agencies, industry and universities.
2. The reports which are listed in R & D Abstracts are catalogued in TIL by author, originator, report number, title, subject (Universal Decimal Classification) and contract and project numbers.
3. The suffix CVD shown after the TIL reference number of certain items indicates that the report in question was selected by the Department of Naval Physical Research (CVD) (Ministry of Defence) representative in Washington, or is issued in connection with CVD-sponsored work.
4. Requests for reports, quoting the TIL Reference Number given at the top left of each item, should be addressed to:-

The Secretary,  
Ministry of Technology,  
TIL , Block A,  
Station Square House,  
St. Mary Cray,  
Orpington, Kent.

5. The circulation of some of the reports listed is subject to special restrictions. Requesters of such reports may have to provide a need to know before the documents can be supplied to them.
6. Enquiries on editorial matters only (not requests for reports, see (4) above), should be addressed to:-

The Secretary,  
Ministry of Technology,  
TIL H, Room 508,  
Block A,  
Station Square House,  
St. Mary Cray,  
Orpington, Kent.

Best Available Copy

# CONTENTS

	Page
Acoustics & Vibrations	21
Aerials	-
Aerodynamics	14
Aerospace Engineering - General	-
Aircraft	46
Aircraft Equipment & Flight Control Systems	45
Aircraft Instruments	45
Air Transport; (includes Air Traffic Control)	46
Ammunition	-
Astronomy & Cartography	7
Biology & Medicine	3
Cables	-
Chemical, Biological & Radiological Warfare	43
Chemistry	25
Circuits - Pulse, Digital, Printed & Potentiometer	36
Communication Systems	-
Communication Theory	28
Computers & Data Processing	4
Containers & Packaging	-
Corrosion & Protection	-
Documentation	1
Electrical Engineering - General	29
Electrical Power (includes Batteries & Fuel Cells)	30
Electrical Testing & Instruments	32
Electricity & Magnetism	28
Electroacoustic Apparatus	-
Electromagnetic Propagation	29
Electron Tubes	37
Electronic Components	-
Electronic Countermeasures	-
Engines - (Piston, Turbine, Ramjet)	39
Explosives & Propellants	44
Fires & Firefighting	3
Fluid Dynamics	12
Food	-
Fuel & Heating	-
Geology & Geophysics	12
Guided Missiles	-
Health & Safety	3
Heat, Thermodynamics, Combustion	22
Hydraulic Fluids	-
Instrumentation	26
Insulators, Dielectrics	-
Land Transport & Vehicles	-
Lines, Networks, Filters & Waveguides	34
Lubrication & Bearings	40
Machine Tools, Machining	-
Magnetic Devices & Materials	33
Materials (Non-metallic)	54
Mathematics	3
Mechanical Engineering - General	39
Mechanical Properties of Materials	52
Mechanics	-
Metallurgy	56
Meteorology	9
Military Engineering - General	42
Military Science	42
Military Vehicles	-
Miscellaneous	60
Navigation	-
Nuclear, Atomic & Molecular Physics	24
Nuclear Reactor Technology & Nuclear Engineering	-

# CONTENTS

	Page
Operations Research .....	1
Optics & Infra-red Systems .....	22
Oscillators & Amplifiers (includes Lasers & Masers) .....	35
Parachutes .....	-
Photography .....	21
Plasma Physics .....	1
Psychology .....	-
Quartermaster Equipment .....	38
Radar .....	37
Radio .....	-
Radomes .....	-
Recorders .....	43
Rockets (includes Rocket Engines) .....	30
Semi-Conductors, Transistors .....	-
Servomechanisms .....	-
Small Arms & Guns .....	38
Space Communication .....	49
Spacecraft .....	46
Space Science .....	44
Structural Engineering .....	-
Television .....	53
Testing of Materials .....	33
Thermo- & Photo-electricity .....	-
Training .....	-
Water Transport & Ships .....	41
Workshop Practice .....	-

P 146159 FR N66-34316 UNLIMITED  
 NASA CR 65454  
 Computer Sciences Corp., El Segundo, Calif., 025.5  
 U.S.A. 629.78 AFOLLO  
 INFORMATION RETRIEVAL AND ENGINEERING AIDS NLS 9-3710  
 SYSTEM

15.7.1966 15pp.  
 The IR and EA System was designed to process, catalogue, edit and report the immense volumes of engineering data generated in the development and construction of Manned Spacecraft Systems for the Apollo Spacecraft Programme. The data involved includes complete descriptive information of development, test, and flight models, as well as ground support equipment.

VJB

### PSYCHOLOGY

NASA SP 128 UNLIMITED  
 National Aero & Space Admin., U.S.A.  
 SECOND ANNUAL NASA-UNIVERSITY CONFERENCE ON 061.3 "3.1966"  
 MANUAL CONTROL (28.2 - 2.3.1966) 621-52  
 417pp. 159.946

Contains the proceedings of the Second Annual NASA-University Conference on Manual Control held February 28 to March 2, 1966, at Cambridge, Massachusetts. The programme was divided into the following nine sessions; discrete and continuous models, adaptive control, information theory, multivariable control, display, motion and stress, applications, optimal control, and analysis and design methods. Both formal and informal presentations were made. All of the formal and some of the informal papers are included.

VJB

### OPERATIONS RESEARCH

AD 634310 R.R.73 UNLIMITED  
 Carnegie Inst. of Tech., Graduate School of  
 Industrial Admin., U.S.A. 65.012.1  
 OPERATIONS RESEARCH IN THE DESIGN OF 016  
 MANAGEMENT INFORMATION SYSTEMS HQR 760(24)  
 Kriebel, C.R.  
 April, 1966 25pp., 77ref.

Surveys a representative selection of the literature on management information systems in which mathematical models are employed as the basis for analysis and system design.

VJB

P 146405 AFSC M 375-1 UNLIMITED  
 Air Force System Command, Washington, D.C.,  
 U.S.A. 65.012.4  
 SYSTEMS MANAGEMENT. CONFIGURATION MANAGEMENT  
 DURING DEFINITION AND ACQUISITION PHASES  
 1.6.1964 356pp.

This manual establishes policy, provides guidance, and assigns responsibilities for configuration management of system/equipment programmes. It prescribes typical formats, authorizes certain forms for preparation and maintenance of system/equipment programme specifications. It provides for making concurrent decisions to approve or disapprove changes in specified requirements and to approve or disapprove the development, production, and retrofit requirements of engineering changes, and for implementing these decisions. It provides for configuration accounting of a given mission, design, series (R/D/S) of a system/equipment programme.

STB

P 146404 AFSCM 375-5 UNLIMITED  
 Air Force Systems Command, Washington, D.C.,  
 U.S.A. 65.012.4  
**SYSTEMS MANAGEMENT. SYSTEMS ENGINEERING  
 MANAGEMENT PROCEDURES**  
 10.3.1966 225pp.  
 Establishes the requirements, policies, and procedures for SPO management  
 of the system engineering effort. It is the system engineering management  
 standard for all future AFSC system acquisition programs, and projects.  
 STB

P 146403 AFSCM 375-4 UNLIMITED  
 Air Force Systems Command, Washington, D.C.,  
 U.S.A. 65.012.4  
**SYSTEMS MANAGEMENT. SYSTEM PROGRAM  
 MANAGEMENT PROCEDURES**  
 31.5.1966 190pp.  
 Establishes the requirements, policies, and procedures for the conceptual,  
 definition, acquisition, and operational phases of a system program. It  
 prescribes the significant management actions for integrating and fulfilling  
 the responsibilities of the organizational elements involved in managing a  
 system program. It is the mandatory management standard for all future  
 AFSC system programs and projects.  
 STB

P 146218 UNLIMITED  
 Boeing Co., Aerospace Group, Seattle, Wash.,  
 U.S.A. 061.3 (3.1967)  
**PROJECT EXPERIENCE IN THE APPLICATION OF SYSTEM  
 EFFECTIVENESS. ASSURANCE MANAGEMENT PRINCIPLES.**  
 (PRESENTED AT THE 2nd EIA SYSTEM EFFECTIVENESS  
 CONFERENCE, FEB.28-MARCH 1, 1967,  
 LOS ANGELES, CALIF.)  
 MacDonald, K.A.B., Ball, L.H.  
 13pp.  
 Successful program managers in a wide variety of projects have recognized  
 the need for their staff to include a technical assurance function as well  
 as a cost assurance and a schedule assurance function. The titles for  
 such positions are usually "System Effectiveness Assurance Manager" or  
 "Product Assurance Manager", but other titles have been used. The duties  
 of the position vary with the phase of the program, but in all cases the  
 result is to give the program manager and his customer confidence that  
 everything that should be done to achieve system effectiveness can be, will  
 be, is being, or has been done. Tangible evidence that this is so is pro-  
 vided by identifying, requiring and validating or when necessary providing  
 appropriate data.  
 VJB

AD 633939 P 3358 UNLIMITED  
 Rand Corp., Santa Monica, Calif, U.S.A. 658.5.01  
**TOWARDS AN IMPROVED BASIS OF ESTIMATING AND  
 CONTROLLING R AND D TASKS**  
 Hill, L.S.  
 May, 1966 19pp., 8ref.  
 Effective managerial control requires that planning at all stages be  
 accepted by both researchers and management. Some of the traditional  
 approaches to recording and analysis of technological development pro-  
 grams are satisfactory if properly used, but complementary techniques  
 are needed to accommodate the unique characteristics of research activi-  
 ties. In the technological development area, it is especially important  
 for control purposes that the complex of program objectives and sub-  
 objectives be clearly identified and that uncertainty be dealt with in an  
 explicit fashion. The techniques for management control suggested in this  
 paper should not interfere with creative activity but, on the contrary,  
 might help to direct the researcher in the conduct of his work.  
 LBT

## BIOSCIENCE

ON CAPTURE OF FISH BY SONAR  
Bureau of Fisheries & Survey, Wash.,  
U.S.A.  
HYPERBARIC OXYGENATION BIBLIOGRAPHY CURRENT  
TO 1965  
20.6.1965 21pp., c.250ref.

UNLIMITED  
016:  
015.805

References, mainly to published literature, arranged in order of author.

FBI

## HEALTH & SAFETY

ORON Rep. 67/10  
U.K. Scientific Mission, Washington, D.C.,  
U.S.A.  
THE SOUTHWEST WATER LABORATORY  
GRIFFITHS, D.L.  
Jan., 1967 6pp.

UNLIMITED  
614.77  
532.95  
597

This Laboratory is one of those under the Federal Water Pollution Control Administration. The field organization of FWPCA is described. Research projects at the Laboratory include (a) biological effect of pesticides on fish (b) estimation of pesticides in water (c) Pearl River Reservoir project.

FAM

## FIRE & FIREFIGHTING

P 146690 NRL Rep. 6499  
Naval Res. Lab., Washington, D.C., U.S.A.  
THE PERMEABILITY AND FLUTRATION METHODS FOR  
DETERMINING THE SPECIFIC SURFACE OF DRY  
CHEMICAL FIRE-FIGHTING POWDERS  
Horta, H.B.  
20.1.1967 22pp., 7ref.

UNLIMITED  
614.043  
539.215.3

The air permeability (Bainbridge) method gives a direct measure of the total surface of a powder sample. The air elutriation (Roller) method gives the distribution of particle diameters in a sample, from which the surface can be found by numerical or graphical integration. Measurements of the specific surface by the permeability method of powders ranging from approximately 2600 to 5900 cm<sup>2</sup>/g were reproducible to within ±1.5% when the test was carried out in a preferred manner. Samples which were frequently exposed to the atmosphere by repeated opening of their containers over a period of a few months suffered an apparent loss of specific surface which could be only partially restored by agitation. Samples which were stored in continuously closed containers showed no change over the same period of time. Mixtures of equal weights of two powders of different composition and different grain shapes gave experimentally determined values of specific surface in good agreement with the average calculated from the specific surfaces of the individual powders. The elutriation method appeared to be unsuitable for characterizing dry chemical powder extinguishants. FBI

## MATHEMATICS

AD 638656 MRC TSR 625  
Wisconsin Univ., Mathematics Res. Center,  
Madison, U.S.A.  
ON SPLINE FUNCTIONS - WITH SUPPLEMENT  
Schoenberg, I.J., Grigilio, T.N.C.  
May, 1956 52pp., 17ref.

UNLIMITED  
512.3  
DX 11-022 ORD 2059

It is shown how spline functions allow one to generalize the Bernstein polynomials, thereby also leading to variation diminishing approximation methods which converge faster than the Bernstein polynomials.

VJB

# COMPUTERS & DATA PROCESSING

NASA TR X-57637      N66-27933      UNLIMITED  
National Aero. & Space Admin., U.S.A.  
DESIGN OF COUNTUP-COUNTDOWN MACHINES      681.3.06  
Moshos, G.J.      511.1  
1965      144pp., 19ref.

The design of a class of special purpose computing machines which compute by counting is systematically developed. The basis of the design philosophy is to limit the basic building elements to three fundamental units and to develop the method of synthesis such that these three building elements are represented as operational units. In particular, the three basic building elements are: (1) the binary rate multiplier which is a means of scaling down a pulse stream to some specified fraction; (2) the counter; and (3) the anti-coincidence circuit which is a means of separating pulses arriving at the counter simultaneously.

VJB

AD 636396      RAC-TP-196      UNLIMITED  
Research Analysis Corp., McLean, Va., U.S.A.  
7040 SIMSCRIPT: A CASE STUDY      681.3.06 SIMSCRIPT  
Weinert, A.E., Bossanga, J.R.      D. 44-188-ARO-1  
Feb., 1966      117pp., 8ref.

Simscript is a computer language designed to aid in the preparation of computer programs for a specific type of problem. Comparisons are made in terms of a particular problem programmed both in Simscript and Fortran IV.

VJB

AD 636435      352.14-R-2      UNLIMITED  
Muller, Raymond & Brown-Singer Inc. State  
College, Pa., U.S.A.      025.5  
A GENERAL MODEL FOR SIMULATING INFORMATION      681.3.06  
STORAGE AND RETRIEVAL SYSTEMS      NCR 38 18(00)  
Blunt, C.R., Duquet, R.T., et al.  
April, 1966      184pp., 8ref.

Presents the results of a research effort to explore the use of computer simulation as a quantitative tool for planning, analyzing and evaluating Information Retrieval (IR) systems. A general time-flow model has been developed that enables a systems engineer to simulate the interactions among personnel, equipment and data at each step in an information processing effort. The input parameters for the simulation reflect the configuration of the system, the processing load of the system, the work schedule of the system, the work schedule of the personnel, equipment availability, the likelihood and effect of errors in processing and the location and availability of the system user.

VJB

AD 634371      MTP-33      ESD-TR-66-289      UNLIMITED  
Mitre Corp., Bedford, Mass., U.S.A.  
AESOP: A GENERAL PURPOSE APPROACH TO REAL-      681.3.06  
TIME, DIRECT ACCESS MANAGEMENT INFORMATION      025.5  
SYSTEMS      65.01  
Spiegel, J., Summers, J.K., et al.      AF 19(628)-5165  
June, 1966      31pp.

AESOP, a laboratory-based prototype of a general purpose, on-line, visually-oriented information system, is used to investigate ways of handling many different types and levels of command and management problems spanning organizational levels from the executive suite down through the staff and operations analysts to the actual system designers and programmers. In particular, it deals with those organizational activities that require highly flexible, direct-access capabilities.

VJB



RAE TR 66255      SPACE 166      UNLIMITED  
 Royal Aircraft Est., Ministry of Aviation, U.K.  
 THE DYNAMIC MODEL OF PROP, A COMPUTER PROGRAM      531.352  
 FOR THE REFINEMENT OF THE ORBITAL PARAMETERS OF      681.3.06 FORTRAN  
 AN EARTH SATELLITE (Presented at COSPAR 7th      061.3 \* 5.1966\*  
 International Space Science Symposium, Vienna, May, 1966)  
 Marsden, R.H.  
 Aug., 1966      30pp., 9ref.

PROP is the code-name for a new orbit determination program written in FORTRAN for an ATLAS computer. With certain minor modifications the program can also handle certain tracking network assessment problems and prediction problems. PROP is similar, in many respects, to the D.O.I. programme of the Smithsonian Institution Astrophysical Observatory, which is based on the theory of Kozai. PROP, however, is capable of handling not only range and angle observations but also observations of range rate and angle rate, so that virtually all current types of ground-based satellite observations can be analysed.

(continued)

RAE TR 66255 (continued)

This paper is concerned mainly with extensions and modifications of Kozai's theory in respect of perturbations due to the gravity field of the earth. In particular, the long-periodic perturbation of the mean anomaly is derived, and compact formulae for perturbations due to zonal harmonics up to any order are presented in a form suitable for computation. Particular attention is paid to the removal of singularities at  $e \approx 0$ ,  $i \approx 0$  and to the pseudoresonance at  $i \approx 63\text{deg.}4$ .

VJB

AD 636738      NWL Rep. 2035      UNLIMITED  
 Naval Weapons Lab., Dahlgren, Va., U.S.A.  
 DA-WRCA: A FORTRAN IV PROGRAM FOR      519.653  
 MULTIPLE LINEAR REGRESSION      681.3.06 FORTRAN  
 Alt, K., Gemmill, C., et al.      519.651.2  
 March, 1966      207pp., 12ref.

Dahlgren-Multiple Regression Comprehensive Analysis is partially based on the Tennessee Valley-WRCA. A multiple linear regression program is given for up to 50 independent variables written in Fortran IV for the IBM 7030 (STRETCH) computer. An outline of the applicability of program includes non-orthogonal analysis of variance.

VJB

NASA TR X-55523      X6-30346      UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 A COMPUTER PROGRAM FOR CALCULATING THE      533.694.541  
 AERODYNAMIC CHARACTERISTICS OF FINS AT      681.3.06  
 SUPERSONIC SPEEDS  
 Barrowman, J.S.  
 April, 1966      35pp., 6ref.

By numerical solution of Busemann's Second Order Aerofoil Theory and the spanwise summing of aerofoil strips, FIN determines the pressure coefficient distributed over a given fin configuration moving at supersonic speeds. In determining the distribution, the program can include the effect of a fin-tip Mach cone. From this basic calculation, FIN can determine as functions of angle of attack the lift coefficient, wave drag coefficient, pitching moment coefficient, and centre-of-pressure location, and as a function of fin cant angle the rolling moment coefficient.

VJB

AD 607408

NL TR 64-52  
Vol.2.

UNLIMITED

International Business Machines Corp., Space  
Guidance Center, Oswego, N.Y., U.S.A.  
AUTOMATED DIGITAL COMPUTER PROGRAM FOR  
DETERMINING RESPONSES OF ELECTRONIC SYSTEMS  
TO TRANSPARENT NUCLEAR RADIATION. VOLUME II:  
PREDICT CIRCUIT ANALYSIS PROGRAM

681.3.06 PREDICT  
539.1.044  
J Q3927: 10853  
Proj.5776  
AF 29(601)5399

Aug., 1964 152pp., 8ref.

PREDICT is an IBM 7090/7094 program which automatically solves, from a description of the network topology, built-in differential and algebraic matrix equations which completely characterize the behaviour of a complex network. The general approach in the PREDICT formulation does not limit it to radiation applications: the radiation problem is treated as a special case of the general circuit analysis problem. Contains information useful to circuit analysts and computer programmers for application of this program. A detailed description of PREDICT, a discussion of its use and operation, and example problems are included to demonstrate and verify its operation at other computing facilities. The last section contains information on machine requirements and off-line equipment necessary for the PREDICT system.

DMA

AD 630301 RM 4762 PR

UNLIMITED

Rand Corp., Santa Monica, Calif., U.S.A.  
A COMPUTER-SIMULATION OF ADAPTIVE ROUTING  
TECHNIQUES FOR DISTRIBUTED COMMUNICATIONS  
SYSTEMS

681.3.06 FORTRAN  
621.39  
AF 49 (638)1700

Boehm, B.W., Mobley, R.L.  
Feb., 1966 44pp., 2ref.

Describes a computer model of a distributed communications system, written in FORTRAN IV and designed to test various adaptive message routing techniques. The program simulates the progress of messages through the system and measures the effects of adaptation of the routing techniques to specified degrees of destruction of its links and nodes. Details of the program are given, plus a list of pitfalls to avoid in developing similar programs.

VJB

AD 635249 Thesis

UNLIMITED

Texas Agricultural & Mechanical Univ., U.S.A.  
PROBABILISTIC MANPOWER FORECASTING  
Kunce, J.F.  
May, 1966 71pp., 33ref.

681.3.06  
650.5.01

A computer program is developed to build a cumulative probability table of all possible combinations of manpower requirements that may occur for a specified group of projects. It is assumed that a manpower array has previously been generated which contains the total manpower requirements, time adjusted, for all the projects to be considered; and the subjective probabilities are available for each project in the array.

LBT

AD 636419

UNLIMITED

Carnegie Inst. of Tech., Pittsburgh, Pa.,  
U.S.A.  
A DEFINITION OF FORMULA ALGOL  
Parlis, A.J., Iturriaga, R. et al.  
29-31.3.1966 46pp.

681.31 CDC G-20  
681.3.06 ALGOL  
ED-146

Formula Algol is an extension of ALGOL 60 incorporating formula manipulation and list processing. A current version of the Formula Algol language which is implemented on the CDC G-20 is defined.

VJB

P 146342 AFRL 66-695 PHSRP 275 UNLIMITED  
 Air Force Cambridge Res. Labs., Hanscom Field,  
 Mass., U.S.A. 681.325.53  
 AVERAGE DIGIT ERROR PROBABILITY AFTER DECODING  
 RANDOM LINEAR CODES  
 Pierce, J.N.  
 Oct., 1966 32pp., 3ref.

The post-decoding digit error probability averaged over all linear codes is compared with the average word error probability. It is shown that the ratio of these two averages approaches a nonzero limit with increasing code length at fixed code rate, and the value of the limit is determined.

VJB

# ASTRONOMY & CARTOGRAPHY

NASA MISC 298 N63-19369 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 THE ORBITING ASTRONOMICAL OBSERVATORY AND THE 522.15  
 ORBITING SOLAR OBSERVATORY 629.783  
 Rosen, N.O.  
 14.8.1963 13pp.

The Orbiting Astronomical and the Orbiting Solar Observatories are designed to permit astronomers to observe the sun, planets, stars, and galaxies from outside the disturbing influences of the earth's atmosphere. To understand why such observations are important, the ways in which the atmosphere hinders observations are reviewed.

VJB

P 146445 Rep. 8346 (1) NASA CR 75299 UNLIMITED  
 N66-26819 FR  
 Parkin-Elder Corp., Electro-Optical Div., 522.15  
 Norwalk, Conn., U.S.A. 629.783  
 PRINCETON ADVANCED SATELLITE STUDY, VOL. 1. INR 31-001-044  
 SUMMARY (8.3.1965-15.5.1966)  
 Loening, W.F., Hanstreet, H.B.  
 35pp.

Contains: General problems associated with spaceborne telescopes; 40-inch system description; OAO/AEP in association with AAP; Recommendations for additional effort; Selected design parameters.

VJB

RAE TR 66257 SPACE 167 UNLIMITED  
 Royal Aircraft Est., Ministry of Aviation,  
 U.K. 531.352  
 SYMMETRY OF A GEOCENTRIC DUST BELT AND THE 523.161  
 ZODIACAL LIGHT 523.59  
 Allen, R.R., Cook, G.E.  
 Aug., 1966 10pp., 7ref.

The behaviour of dust particles in geocentric orbits is discussed. An approximate analytical solution can be found for the motion under gravitational forces alone if the orbital eccentricity is small, and a plane of symmetry can be defined if the lunar orbit is assumed fixed. Solar radiation pressure is important for dust particles and its effect is to change the position of the plane of symmetry so that it lies more nearly in the ecliptic. If, as suggested by Peale, a substantial part of the zodiacal light is due to dust particles in geocentric orbits, they must be fairly distant, probably beyond about 12 earth radii.

VJB

RLE TR 66396 SPACE 184 UNLIMITED  
 Royal Aircraft Est., Ministry of Aviation,  
 U.K. 523.3  
 THE ORBITS OF LUNAR SATELLITES: AN 531.352  
 INTRODUCTION  
 Cook, G.E.  
 Dec., 1966 21pp., 20ref.

Present knowledge of the Moon's gravitational field is briefly reviewed. The report then describes the main perturbations of the orbit of a lunar satellite caused by low-order terms in the lunar gravitational potential and by the Earth. Techniques for investigating the lunar potential are outlined.

VJB

NASA TT F-394 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 PROBLEMS IN ASTROPHYSICS: INVESTIGATION OF 061.3 "6, 1964"  
 THE ATMOSPHERES OF VENUS AND MARS 523.42  
 Koval, I.K. 523.43  
 Jan., 1967 148pp., 198ref.

A Conference of the Working Group on Investigation of Earth-Type Planets was held in Kiev in June 1964 to discuss the results of these studies and to point out paths for future investigations. The complete contents of most of the many reports and lectures given at the conference are published in this collection.

VJB

NASA TTF-430 UNLIMITED  
 Academy of Sciences of the Ukrainian SSR,  
 Ukrainian Interdepartmental Collection 523.5  
 Series, Astronomy and Astrophysics 523.6  
 PHYSICS OF COMETS AND METEORS  
 Konopleva, V.P.  
 1965 92pp.

Contents: Photometry of comets using 1963-1964 patrol photographs (Rozhkovskii, D.A.); Detailed photometry of comet Arend-Roland 1956 h (Nazarchuk, G.K.); The radius of existence of  $C_2$  and  $C_3$  molecules in comets (Cherednichenko, V.I.); Dissociation and ionization of water molecules in cometary atmospheres (Cherednichenko, V.I.); Intrinsic brightness of comet Ikeya 1963 a (Vsekhvutskii, S.K.); Visual observations of comet Alcock 1963 b (Vsekhvutskii, S.K.); Statistical characteristics of the meteor radio echo in the epoch of the 1963 Geminids (Fialko, E.I., Bairachenko, I.V. et al);

(continued)

NASA TTF-430 (continued)

Some results of the application of intermediate-type trains in measurements of electron line density (Fialko, E.I., Bairachenko, I.V. et al); Propagation of electromagnetic waves in a moving gyrotropic medium (Daryugin, I.A. and Vorontsov, V.I.); The drift of meteor trains (Kashcheev, B.L.); Some problems of the theory and new methods of observation of meteors (Kramer, E.N.); On the subject of the trajectory and the orbit of the Tunguska Comet (Astapovich, I.S.); Turbulent motions in the upper atmosphere at heights of 80 - 110 km according to radio observations of meteor trains (Delov, I.A.); The Kiev seminar on comet photometry.

LBT

NASA CR 672

Control Data Corp., Minneapolis, Minn., U.S.A.  
A THEORETICAL INVESTIGATION OF INFORMATION  
LIMITS OF SCANNING OPTICAL SYSTEMS

UNLIMITED

523.8

621,377,371.2

Furrell, E.J., Zimmerman, C.D., et al.  
Jan., 1967 352pp., 87ref.

The objectives described are: (1) to improve the accuracy of current methods of predicting system performance, and (2) to develop better techniques of signal processing. The first objective entails selecting models that are more complete than models currently used. With complete models, we can accurately predict system performance. The second objective entails developing processing techniques that efficiently use signals generated by the photodetector. With efficient techniques, the sensor size can be minimized or more accurate measurements obtained.

VJB

AEC TR 66279

SPACE 169

UNLIMITED

Royal Aircraft Est., Ministry of Aviation, U.K.  
RESONANCE EFFECTS DUE TO THE LONGITUDE  
DEPENDENCE OF THE GRAVITATIONAL FIELD OF A  
ROTATING PRIMARY

523.838

534.242

629.783

Allan, R.R.

Aug., 1966

40pp., 21ref.

There will be long-period oscillations in the position of a satellite if its path is nearly repetitive relative to the rotating primary, and there is an infinite sequence of such resonances. The behaviour near resonance is governed by a pendulum equation and in the extreme case a satellite can be captured by the resonance and be stable against small drag forces. Moreover the presence of "drag" forces, which include a change in the primary's rotation, e.g. by tidal effects, gives a mechanism for permanent or semi-permanent capture, a positive real drag or its equivalent being the more favourable condition. If capture takes place, "drag" forces lead to secular changes in inclination; the sense depends on the sign of the drag, whether the resonance is above or below synchronous height, and on the inclination itself. The resonance effects are highly dependent on inclination, and all except the synchronous resonance become ineffective on the equatorial plane. This appears to give a partial explanation of the formation and structure of the rings of Saturn, and suggests that there could be similar but much less regular bands of dust around the earth.

RPF

P 146113 ESRO SN-59

UNLIMITED

European Space Organisation, Paris, France  
OBSERVATION OF STELLAR X-RAY SOURCES

551.521.64

Rossi, B.

551.507.362.1

May, 1966

67pp., 5ref.

523.87

The limitations of X-ray astronomy due to absorption and production of secondary photons in the atmosphere are discussed. Almost all measurements have to be conducted from rockets or satellites. The experiments which have been carried out so far are mentioned. In the second chapter the detectors employed (gas counters, scintillation crystals and photoelectric devices) are described as well as ancillary instrumentation. The analysis of data obtained from rocket flights is extensively discussed. In the last chapter the results of the observations performed until now are presented and compared in detail. The present knowledge on extra-terrestrial non-solar X-ray sources is critically reviewed.

VJB

METEOROLOGY

P 146463 ESRO SN-59 ESRLB

UNLIMITED

European Space Res. Organisation, Paris,  
France

551.507.321

DESCRIPTION OF EXPERIMENT R-74 SARDINIA,  
JULY 1966 INVESTIGATION OF NEUTRON ALBEDO

551.521.14

539.125.5

Page, D.E.

Aug. 1966

9pp., 6ref.

The aim of this experiment is to determine the densities of atmospheric neutrons with energies from thermal (about 0.04 eV) up to about 20 MeV in a height band between 40 and 60 km. Brief mention is made of the scientific reasons for the experiment and of previous measurements from balloons at heights approaching 40 km. The method to be used in the present experiment is to carry the detector up to about 60 km by means of a Bellier rocket and then to eject it attached to a parachute.

VJB



RAE TR 66370 SPACE 101  
Royal Aircraft Est., Ministry of Aviation,  
U.K.

UNLIMITED

COMPARISON OF AIR DENSITIES OBTAINED FROM  
ORBITAL DECAY AND INSTRUMENTS

551.510.3  
531.352

Cook, G.E.

Nov., 1966

23pp., 33ref.

Methods for determining upper-atmosphere density are briefly reviewed. Values of air density derived from orbital decay are compared with those obtained from instruments and shown to be systematically higher. The difference is too large to be due entirely to errors in the drag-derived values and cannot be explained at present if the absolute accuracy claimed for the gauges is realistic. This paper was presented at a Discussion Meeting on Orbital Analysis at The Royal Society, London, 17-18 October, 1966.

VJB

P 146464 ESRO SM-63  
European Space Res. Organisation, Paris,  
France.

UNLIMITED

OBSERVATIONS OF SOLAR X-RAYS

551.521.1  
551.5C7.3

Labeyrie, J.

April, 1966

62pp., 42ref.

537.531

A comprehensive review of the measurements of X-rays emitted by the quiet as well as the active sun is presented. Starting with the historic sounding rocket flight by Burnight in 1948 these observations were carried out by means of balloons, sounding rockets and satellites, covering more than one solar cycle. The instruments used as well as the experimental results are discussed in detail.

VJB

P 146195 TP 72 NSG-16687  
Sci. Ann. Prog. Rep. 2 NASA CR 70053  
Colorado State Univ., Atmospheric Science  
Dept., Fort Collins, U.S.A.

UNLIMITED

551.521.14

551.521.2

THE INVESTIGATIONS OF THE TEMPERATURE AND  
SPECTRAL EMISSIVITY CHARACTERISTICS OF CLOUD  
TOPS AND OF THE EARTH'S SURFACE

NSR-147

(Feb.-Sept., 1964)

Marlatt, W.E.

Dec., 1965

26pp.

During the period measurements of surface temperatures over the Pawnee National Grassland were continued using thermistors, and ground-based and airborne radiometers. Measurements of albedo and of clouds, ocean surfaces and various earth surfaces were obtained using the TIROS radiometer (channel 3 and channel 5) and the sol-a-ceters. Measurements of desert ground radiation and temperatures were obtained near Edwards Air Force Base, California, in conjunction with flights conducted by the CARIE Project and the University of Michigan. Measurements of ocean and grassland-surface temperatures were obtained for several orbits immediately following the launching of NEOSUS I. A few measurements of cloud-top radiation temperatures were obtained for comparison with air temperatures.

LBT

P 146351 Sci. Rep. 4 AFCL 66-812  
Denver Univ., Physics Dept., Col., U.S.A.  
ATMOSPHERIC ABSORPTIONS OVER LONG SLANT PATHS  
IN THE STRATOSPHERE

UNLIMITED

551.521.18

551.507.321.2

Murphy, D.G., Murphy, F.H., et al.

AF 19(628)5202

Oct., 1966

57pp., 5ref.

The variation of the infrared solar spectrum with altitude was observed during a series of balloon flights made from Fairbanks, Alaska. Spectra were obtained at various altitudes with solar zenith angles ranging from 49 to 92 deg. These spectra were used to determine the atmospheric transmittance to be expected at high altitudes and particularly over very long slant paths in the stratosphere. The transmittance data are presented.

VJB

NASA TM X-51611

National Aero. & Space Admin., U.S.A.  
THE LATITUDINAL DISTRIBUTION OF CLOUD COVER  
FROM TIROS III PHOTOGRAPHS

UNLIMITED

629.78 TIROS  
551.576

Arking, A.

July, 1965

16pp., 6ref.

Television pictures from the TIROS III satellite have been analyzed on a computer to give the latitudinal distribution of cloud cover during the summer of 1961. The results, which will be useful in studying the heat balance of the atmosphere, and in the determination of vertical motion, show good agreement with the long term average cloudiness derived from data accumulated during a half-century of ground observations.

LBT

GEOLOGY & GEOPHYSICS

AD 638301 NEL Rep. 1374

UNLIMITED

Navy Electronics Lab., San Diego, Calif.,  
U.S.A.

551.462

PHOTO ANALYSIS OF SEA FLOOR MICRORELIEF

Shipek, C.J.

26.4.1965

70pp., 36ref.

Over 700 NEL sea floor photographs, obtained intermittently over a 10-year period, in a wide variety of environments, have been analyzed. Five major types of bottom microrelief, on the basis of origin, have been defined, a numerical scale of microroughness has been developed and ratings predicted for normal bottom environment and zones of isoroughness have been delineated for large portions of the Pacific and adjacent ocean areas.

LBT

AD 639101 EN 134-12

UNLIMITED

National Engineering Science Co., Pasadena,  
Calif., U.S.A.

016:

A BIBLIOGRAPHY ON STORM SURGES AND RELATED  
SUBJECTS

551.466

NORR 4177(00)

Breitschneider, C.L., Pick, G.S.

1.8.1966

48pp.

Work began on this bibliography in 1960, using the library of the Coastal Engineering Research Center (formerly Beach Erosion Board) of the U.S. Army Corps of Engineers. It was continued and brought up to date under ORR sponsorship under Contract NORR-4177(00), "Modification of Wave Spectra over the Continental Shelf". A report is under preparation on "Storm Surges: Theory, Measurements and Data Collection". This will discuss the effects of the continental shelf on waves.

LBT

FLUID DYNAMICS

P 146194

N66-27079 NASA CR 64421

UNLIMITED

California Inst. of Tech., Jet Propulsion  
Lab., Pasadena, U.S.A.

532.517.4

EXPLORATORY MEASUREMENTS IN SPIRAL TURBULENCE

532.512.2

Van Atta, C.

532.527.2

c.1965

38pp., 5ref.

NAB7-100

These experiments lay a foundation for a study of interface propagation in a mixed laminar-turbulent flow between counter-rotating concentric cylinders. Such mixed flows, including one particularly well-organized pattern called spiral turbulence, are found to be a dominant feature of transition in Couette flow. In spiral turbulence, the laminar and turbulent regions of the flow form an alternating pattern of helical stripes, rotating with approximately the mean angular velocity of the two cylinders. Stable right- and left-handed spirals occur with equal probability when the flow is established from rest. Hot-wire measurements have been made of the mean cross-sectional shape of the interfaces in the axial mid-plane for a spiral-turbulent flow having low dispersion in interface position.

VJB



P 146442 LMSC/HREC A 702436 FR UNLIMITED  
HREC 11924-1  
NACA CR 77547 532.525 AMPLIFICATION  
N66-35232 NBS 8-11924

Lockheed Missiles & Space Co., Huntsville Res.  
& Engineering Center, Ala., U.S.A.

ELECTROFLUID CONVERTER (25.6.1965-25.3.1966)

Chang, C.S., Trautwein, W., et al.

25.3.1966 50pp., 6ref.

Four electrofluid converter concepts were considered and investigated: (1) deflectable splitter; (2) flapper valve; (3) acoustic driver; and (4) movable nozzle. Models of each were built, compared and evaluated. The most promising one, the flapper valve concept, was selected and development work was continued to improve the performance characteristics of this selected model.

VJB

AD 631561 FR UNLIMITED  
Johnson Service Co., Milwaukee, Wis., U.S.A.  
IMPACT MODULATOR, IMPACT MODULATOR AMPLIFIERS 532.525 AMPLIFICATION  
WITH FEEDBACK, AND SYSTEMS APPLICATIONS DA 49-186-412-28(X)  
(15.5.1963 - 30.6.1964)  
15.7.1964 46pp.

The primary objective of this work is to develop and test pure fluid (pneumatic) circuits that perform as operational amplifiers and integrators. The active fluid component is the transverse impact modulator. The basic circuit diagram for the operational amplifier is essentially the same as an electronic operational amplifier. The difference being that the pneumatic DC amplifier has a low input impedance which has to be considered in the analysis. Two operational amplifiers in series are used to attain a positive gain package which is used to form a bootstrap integrator. When properly adjusted this device performs a true integration. The governing equations are presented which describe the resistance values necessary to obtain desired integration rates.

DMA

P 146204 CAL-AD-1672-A-2 ARL 66-0190 UNLIMITED  
Cornell Aeronautical Lab Inc., Buffalo, N.Y.,  
U.S.A. 536.423  
AN ANALYSIS OF THERMAL AND DIFFUSION EFFECTS 532.529  
ON DROPLET GROWTH RATES AF 33(657)-8302  
Kang, S-W., Weatherston, R.C.  
Sept., 1966 62pp., 6ref.

The effects of thermal and diffusion limitations on growth rates and temperature history of small droplets are analyzed for a supersaturated vapour in an inert carrier gas. The growth rates are determined for the cases of (1) constant field conditions, and (2) changing fluid conditions due to vapour deposition on droplets. The analysis is so formulated as to describe the growth process as the droplet size increases from microscopic (free-molecular) to macroscopic (continuum).

VJB

P 146191 O3424-18-T TR-18 UNLIMITED  
NABA CR 75127  
N66-26659 532.529.5  
Michigan Univ., Coll. of Engineering, Ann 532.528  
Arbor, U.S.A. Grant N60-39-60

CHOKED FLOW ANALOGY FOR VERY LOW TWO-PHASE  
FLOWS

Harrist, P.O., Robinson, M.J.  
March, 1966 40pp., 22ref.

Two theoretical models to predict axial pressure distribution, void fraction, and velocity in a cavitating venturi are applied. The theoretical predictions are compared with experimental data from cold water and mercury tests, and good agreement for the pressure profiles is found. The predicted void fractions are found to be too high, probably because the models assume zero slip or negative slip between the vapour and liquid phases.

VJB

AD 633612    OEL TR 66-6    UNLIMITED  
 New York Univ., Geophysical Sciences Lab.,  
 Bronx, U.S.A.    532.593.4  
 ON THE GROWTH OF THE SPECTRUM OF A WIND    551.46.018  
 GENERATED SEA ACCORDING TO A MODIFIED MILES-    535.33  
 PHILLIPS MECHANISM    N 62306-1589  
 Inoue, T.  
 April, 1966    64pp., 26ref.

The need for the study of ocean waves has increased rapidly owing to increased needs in fields like naval architecture, optimum ship routing and coastal engineering. One of the most important problems is the forecasting of sea surface conditions. Ocean Wave problems are not simple, mainly because of the complexity of the turbulence at the interface of the atmosphere and the ocean. Since the introduction of the wave spectrum concept, ocean wave studies have made remarkable progress. Wave forecasting had been done by using an empirical spectral growth relationship. In the late 1950's, two kinds of wave generation mechanisms were proposed. In this paper, an attempt to determine spectral wave growth is reported by the application of two modified wave generation mechanisms based on the theories of Miles and Phillips.

STB

P 146439    QPR 15    N66-34071    UNLIMITED  
                                  NASA CR 77093  
 Southwest Res. Inst., San Antonio, Tex.,    532.595  
 U.S.A.    Proj. 02-1072  
 FUEL SLOSHING STUDIES (1.10-31.12.1964)    NAS 8-1555  
 8.1.1965    7pp.

Tests for determining pressure distributions on a single solid ring baffle have been completed, and the data from these tests are in the final stages of being reduced to an appropriate form for presentation. The experimental apparatus devised for measuring torque, as well as the phase angle between torque and displacement, in a pitching cylindrical tank has now been essentially completed.

VJB

#### AERODYNAMICS

P 146189    CR-332-761-001    N66-39999    UNLIMITED  
                                  FR    NASA CR 79095  
 General Dynamics, Pomona Div., Calif., U.S.A.    532.526.4  
 DIRECT MEASUREMENT OF COMPRESSIBLE TURBULENT    532.526.7  
 BOUNDARY LAYER SKIN FRICTION ON A POROUS FLAT    NAS 7-294  
 PLATE WITH MASS INJECTION  
 Derzhin, H., Leonard, C.A., et al.  
 July, 1966    46pp., 19ref.

An experimental investigation of skin friction on a porous flat plate in supersonic turbulent flow has been carried out. Useful data has been obtained at 3.2 (nominal) and at two of the order of 10%. Measurements were made with a skin friction balance which permitted mass injection through its friction surface. The injectant gas was nitrogen. The results of the experiments are in essential agreement with the theory of Rubesin as regards skin friction reduction with mass injection. In addition, correlation of the skin friction data with heat transfer measurements, conducted previously by Bartle and London, tend to verify the "Raynolds analogy" between skin friction and heat transfer developed by Rubesin.

VJB

NASA SP 106    UNLIMITED  
 National Aero & Space Admin., U.S.A.  
 THE DYNAMIC BEHAVIOR OF LIQUIDS IN MOVING    532.595  
 CONTAINERS  
 Abramson, H.N.  
 1966    467pp.

Contents:- Introduction (Abramson, H.N.); Lateral sloshing in moving containers (Silverman, S., Abramson, H.N.); Nonlinear effects in lateral sloshing (Abramson, H.N., Chu, W.H., Dodge, F.T.); Damping of liquid motions and lateral sloshing (Silverman, S., Abramson, H.N.); Simulation and experimental techniques Part I: Simulation of liquid sloshing (Dalszell, J.F.); Part II: Experimental techniques and apparatus (Brooks, G.W.); Analytical representation of lateral sloshing by equivalent mechanical models (Dodge, F.T.); Vehicle stability and control (Bauer, H.F.); Vertical excitation of propellant tanks (Dodge, F.T.); Interaction between liquid propellants and the elastic structure (Kane, D.D.); Special topics Part I: Liquid impact on tank bulkheads (Dalszell, J.F.); Part II: Liquid rotation and vortexing during draining (Dodge, F.T.); Part III: Longitudinal oscillations of flight vehicles (Kane, D.D.); Liquid propellant behaviour at low and zero g (Raynolds, W.C., Gatterlee, H.H.)

VJB

NASA TM X-53501 N66-38487 UNLIMITED  
National Aero. & Space Admin., U.S.A.  
RESEARCH ACHIEVEMENTS REVIEW, SERIES NO. 12 047.1  
1965 35pp., 7ref. 532.5  
533.6

Contains the following articles:- Subsonic Flow, Jet Impact in water, Base flow investigation, Effect of Wall-to-total temperature ratio on hypersonic flow detachment, Variable Porosity Walls, Dynamic balance for Saturn Forebody, Panel Flotter, Aerodynamic-Damping studies, Buffeting, Engine Generated Noise, Ground-Winds problems, Short Duration techniques in Base-heating, External-flow Reynolds number program, Flow field visualization, Radiation, Investigation of Combustion of hydrogen in a hypersonic air stream, Rarefied Gas Dynamics and Turbulent fluctuation measurements with the Crossed-beam method.

NOP

NASA TM X-56865 N66-29374 UNLIMITED  
National Aero. & Space Admin., U.S.A.  
RECENT RESEARCH RESULTS IN THE AERODYNAMICS 533.6.011.5  
OF SUPERSONIC VEHICLES 629.73 SCAT 15-F  
Robins, A., Morris, O.A., et al.  
Nov., 1965 22pp., 3ref.

The continuing aerodynamic-research effort aimed at improving the design of supersonic-cruise vehicles has recently produced some significant results. Research by both government and industry has provided, in addition to a better understanding of the design problem itself, some new and very useful design tools and concepts. Some of the advantages of these methods in the treatment of wave drag and drag due to lift are briefly discussed. Also presented are some new considerations of aerodynamic interference and its effect on the aerodynamic efficiency of the trimmed vehicle. An illustrative example of the application of these design tools and concepts to the aerodynamic design of a supersonic-cruise vehicle (SCAT 15-F) is made.

YJB

P 146203 ARL 66-0186 UNLIMITED  
Aerospace Res. Labs., Wright Patterson AFB,  
Ohio, U.S.A. 533.6.011.8  
THE LINEARIZED RAYLEIGH PROBLEM IN A 533.5  
RAREFIED GAS FLOW ACCORDING TO THE BOK MODEL 533.73  
Nagaraja, K.S.  
Sept., 1966 98pp., 39ref.

The classical Rayleigh problem has been formulated using the BOK kinetic equation, and the numerical evaluation is carried out on an IBM-7094. The results describe the macroscopic velocity  $u_x$ , the shear stress  $\tau_{xy}$ , the tangential heat flux  $q_x$ , and the temperature field  $T$  in the near-free-molecule flow. These results are obtained for a wide range of values of  $\lambda$  ( $\lambda$  the number of inter-molecular collisions in a time  $t$ ).

YJB

NASA TM X-1198 N66-17888 UNLIMITED  
National Aero. & Space Admin., Washington, D.C.,  
U.S.A. 629.73 X-15A-2  
AERODYNAMIC CHARACTERISTICS OF A 0.0667-SCALE 533.6.013.4  
MODEL OF THE X-15A-2 RESEARCH AIRPLANE AT  
TRANSONIC SPEEDS  
Patterson, J.C.  
63pp.

The Mach number varied from 0.60 to 1.20. Angle of attack range -4 deg. to 20 deg. Reynolds numbers  $2.07 \times 10^6$  to  $2.172 \times 10^6$ . Static longitudinal, directional, and lateral stability has been reduced at lifting conditions compared with that of the X-15 research aircraft, when the external fuel tanks are absent.

NOP

NASA TIL 6803

N66-31728

UNLIMITED

NASA MEMO 2-3-59L

National Aero. & Space Admin., U.S.A.  
COMPARISON OF CONTROL-FIXED STABILITY  
DERIVATIVES FOR TWO SUPERSONIC FIGHTER AIRPLANES  
AS DETERMINED FROM FLIGHT AND WIND-TUNNEL TESTS

533.6.013.4

629.735.33

Crane, M.L., McLaughlin, M.D., et al.

April, 1959 33pp., 1ref.

The principal control-fixed stability derivatives of two fighter aircraft operating in the 'clean' condition have been obtained from flight tests at an altitude of 35,000 feet at M up to 1.44 for one aircraft and up to 1.27 for the other aircraft. The static derivatives were compared with those determined from wind-tunnel results after the tunnel data were adjusted for the effects of differences in configuration, aeroelastic distortion, and mass flow through the engine. After these adjustments were made, the static derivatives determined from the wind-tunnel results usually proved to be an adequate indication of the derivatives of the full-scale aircraft.

VJB

NASA TT F-10204

N66-29728

UNLIMITED

National Aero & Space Admin., Washington, D.C.  
U.S.A.

629.7.025.4

FLIGHT HANDLING QUALITY PROBLEMS POSED BY  
SWEEP-WING TRANSPORT PLANES WITHOUT TAIL UNITS

629.734.3

629.7.072

Looze, P., Page, E.

533.6.015

June, 1966 59pp., 22ref.

Analyses the unusual features of swept-wing tail-less, heavy aircraft, from the pilots viewpoint. Emphasis is put on the special low velocity type of behaviour, in connection with the longitudinal flight qualities.

RPF

S &amp; T Memo 9/66

UNLIMITED

Technical Information & Library Services,  
Min. of Aviation, U.K.

533.6.015.1

THE DRAG OF A LARGE AND SMALL PNEUMATIC TYRE  
TRAVELLING THROUGH WATER, SLUSH AND SNOW

656.71:551.578.1

539.622

SUGB, R.W.

629.7.027.23

Oct., 1966 8pp., 1ref.

Tests were made with a 35 x 10 - 17 aircraft tyre, using the heavy load test which described in S & T Memo 8/63 and results were compared with those from a 13 in. diameter, 3 in. wide tyre in trials of a recently developed device, a slush drag meter to measure the water equivalent depth of runway contamination. Trials were conducted at Bromma, Sweden, on natural snow and at Road Research Laboratory, Crowthorne and Bristol University on water and ground ice with the small tyre and slush drag meter, and at Crowthorne only with the aircraft tyre. Within the speed range of the tests (up to 90 ft/sec.) it was found that drag varied linearly with velocity squared in water and ground ice with both tyres and with the small tyre in Swedish snow. With the small tyre drag per inch increased with depth but was constant with the large tyre.

RHE

RAE TR 66356

AERO 2856

UNLIMITED

Royal Aircraft Est., Ministry of Aviation, U.K.  
CALCULATION OF THE LOAD DISTRIBUTION, AT  
SUPERSONIC SPEEDS, ON A SWEEPBACK WING OF  
ARBITRARY PLANFORM

533.6.048.1

533.693.1

533.6.048.3

Roper, O.H.

Nov., 1966 10pp., 37ref.

The swept back wing can be cambered or uncambered, with subsonic leading edges and supersonic or subsonic trailing edges. Evvard's method is used for the part of the wing ahead of the trailing edge disturbances, and a lift cancellation method for the part affected by the wake. The formulae derived are put into forms suitable for calculations on a high speed digital computer.

RPF

AD 636392 AFTR 6273 UNLIMITED  
 Air Force Systems Command, Flight Test  
 Center, Edwards AFB., Calif., U.S.A. 533.6.053  
 FLIGHT TEST ENGINEERING HANDBOOK. 083  
 CORRECTED AND REVISED JUNE 1964-Jan. 1966  
 Herrington, R.M., Shoemaker, P.E., et al.  
 May, 1951 660pp.

Methods of obtaining flight test data for reciprocating engine aircraft (including helicopters) and turbojet aircraft are presented together with various methods of data analysis and data presentation. Correction of aircraft performance to standard conditions is included, as are detailed derivations of correction factors and performance parameters. Numerous graphs and charts containing information required by and useful to the flight test engineer are presented, together with sample data reduction forms and sample flight test programs.

VJB

NASA TM X-1278 N66-34426 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 CHARACTERISTICS OF A NEW TYPE BALANCE FOR 533.6.071.3  
 WIND-TUNNEL MODELS

Dineff, J., McFarland, K., et al.  
 15.6.1966 24pp.

A new type of internal-sting, six-component, strain-gauge balance has been developed and calibrated at Ames Research Center. The balance is used to measure the aerodynamic forces on wind-tunnel test models. A unique feature of the balance is a hollow cavity running the length of the balance, through which additional wires, linkages, hydraulic lines, etc., can be passed. Other attractive features include the ease of aligning the force elements, and the ability to fabricate the assembly with standard machine shop tooling. These features are made possible by the relatively simple geometry with all elements being machined in one piece.

VJB

AD 640945 Rep. 756 USAAVLABS TR 66-53 UNLIMITED  
 Princeton Univ., Aerospace & Mechanical  
 Sciences Dept., N.J., U.S.A. 533.652.6  
 AN ANALYTICAL STUDY OF FACTORS INFLUENCING THE 533.6.013.412  
 LONGITUDINAL STABILITY OF TILT-WING VTOL 629.735.3  
 AIRCRAFT 629.73 Xc-142A  
 Bopp, G., Curtiss, H.C. DA 44-177 AMC-8(T)  
 July, 1966 90pp., 22ref.

An analytical method for predicting the stability characteristics of tilt-wing VTOL aircraft in the transition speed range is presented. Sample calculations based on an assumed tilt-wing VTOL transport configuration of the XC-142A class with double-slotted flaps are given. A limited comparison of the calculated results with experimental data obtained from a dynamic model of the XC-142A, which is somewhat dissimilar from the assumed configuration, is presented. This comparison indicates that the trends of the stability derivatives are correctly predicted. The agreement between theory and experiment is good in hovering; however, as the wing incidence is reduced, the difference between theory and experiment becomes quite large.

STB

NASA CR 713 UNLIMITED  
 Arizona State Univ., Tempe, U.S.A.  
 ON THE DYNAMIC CHARACTERISTICS OF A VARIABLE- 533.665  
 MASS SLENDER ELASTIC BODY UNDER HIGH 533.696.3  
 ACCELERATIONS 624.074.7

Melrovitch, L., West, D.A.  
 Feb., 1967 76pp., 28ref.

The dynamic characteristics of a slender, elastic body of variable mass were investigated. The analysis is applicable to a solid-fuel missile which was envisioned as a slender, cylindrical body capable of both rigid-body motion as well as axial and transverse elastic deformation. During the powered flight of the vehicle, the mass was considered as a function of time with the products of combustion flowing relative to the missile structure and finally exhausting through a nozzle to the atmosphere.

MHC

AD 635468 DTIC Rep.21218 Rep.Aero 11008 UNLIMITED  
 David W. Taylor Model Basin, Aerodynamics Lab.,  
 Washington, D.C., U.S.A. 629.1.039  
 SOME DESIGN PRINCIPLES OF GROUND EFFECT 533.68  
 MACHINES, SECTION B, AIR CUSHION MECHANICS  
 Chaplin, H.R., Ford, A.G.  
 April, 1966 40pp.

The energy and momentum relationships governing air cushion performance are reviewed. The exponential-theory equations are recommended for calculation of cushion pressure and jet reaction, and a modified equation is proposed for calculation of the volume flow rate. The question of off-design cushion performance is discussed. It is pointed out that off-design performance is of paramount practical importance and that the widely held notion that peripheral jet cushions are more efficient than simple plenum cushions is not necessarily valid in this context. The danger of drawing erroneous conclusions from the cushion performance equations, which (except for the plenum) do not apply to off-design operation, is emphasized.

ZHR

NASA TM X-743 N66-34954 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 SUBSONIC AND SUPERSONIC AERODYNAMIC 533.693.49  
 CHARACTERISTICS OF AN AIRPLANE CONFIGURATION  
 UTILIZING DOUBLE-PIVOT VARIABLE-SWEEP WINGS  
 Polhamus, E.C., Alford, W.J., et al.  
 Dec., 1962 53pp., 6ref.

A variable-wing-sweep aircraft having a double-inboard-pivot wing has been tested at low subsonic speeds and at a Mach number of 2.20 to determine the aerodynamic characteristics of this type of configuration. The double-pivot wing consists of a main wing and a fore wing, each pivoted within the fuselage in such a manner that unbroken leading and trailing edges are provided in both the low- and high-sweep positions. The results indicate that the variation of longitudinal stability with wing sweep angle for the double-pivot wing was similar to that of an outboard-pivot wing and considerably less than that of a single-inboard-pivot wing investigated in combination with the identical fuselage and tail arrangement.

VJB

P 146409 D6-19860 NASA CR 62037 UNLIMITED  
 N66-32623  
 Boeing Co., Renton, Wash., U.S.A. 533.693.49  
 367-80 VARIABLE STABILITY SIMULATION SYSTEM 629.7.025.3  
 (NASA Ames Large Transport Simulation Program) 629.73 BOEING 707  
 Baska, G.W., Robbins, R.E. NAB2-3224  
 25.1.1966 161pp., 5ref.

Describes the simulation systems as used for the NASA Ames program and includes descriptions of the technique, hardware, operational procedure and the various configurations simulated.

VJB

P 146414 D6-19856 N66 31853 UNLIMITED  
 NASA CR-66126  
 Boeing Co., Renton, Wash., U.S.A. 533.693.49  
 367-80 AIRPLANE VARIABLE STABILITY SIMULATION 629.735 ((629.7.016.54))  
 SYSTEM (NASA Langley Supersonic Transport NAB1-4096  
 Simulation Program)  
 Robbins, R.E., Person, S.D.  
 10.2.1965 204pp., 2ref.

Describes the techniques, hardware and operational procedures involved in the variable stability programs. Also included is a description of the SST configurations that were simulated and flight tested and a discussion of some of the problems encountered.

VJB

P 146410 D6-10743 NASA CR 66125  
N66-31854

UNLIMITED

Boeing Co., Renton, Wash., U.S.A.  
SIMULATION OF THREE SUPERSONIC TRANSPORT  
CONFIGURATION: WITH THE BOEING 367-80  
IN-FLIGHT DYNAMIC SIMULATION AIRPLANE

533.693.49  
629.754(629.7.016.54))  
NAS 1-4096

Elbridge, W.H., Cond't, P.H., et al.  
28.12.1965 202pp.

Three supersonic transport configurations were evaluated with the Boeing 367-80 in-flight dynamic simulation aircraft. Typical variable geometry and delta SST configurations in landing approach configuration were simulated and evaluated in detail. In addition a variable geometry aircraft in an emergency wings back configuration (72 deg. sweep) was briefly evaluated. In this programme the basic SST configurations were evaluated and systems of longitudinal and lateral-directional stability augmentation were developed and evaluated. (The 72 deg. sweep was tested in the basic configuration only). The effect of centre of gravity position was evaluated with and without longitudinal stability augmentation. Configurations with degraded lateral-directional stability were evaluated to anticipate the possible variations with SST configuration changes or inaccuracies in estimating the stability derivatives.

VJB

NASA TM X-280

N66-21563

UNLIMITED

National Aero. & Space Admin., U.S.A.  
TRANSONIC WIND-TUNNEL INVESTIGATION OF THE  
EFFECT OF CONTROL SPAN AND LARGE WING-TIP  
NACELLES ON EFFECTIVENESS OF SPOILER-SLOT-  
DEFLECTOR CONTROLS ON AN UNSWEPT-WING FIGHTER-  
TYPE AIRPLANE

533.694.27  
533.6.013.153

Hornon, D.E.

May, 1960 29pp., 5ref.

An investigation was conducted in the Langley 8-foot transonic pressure tunnel to determine the effect of control span and large wing-tip nacelles on spoiler-slot-deflector effectiveness. Effect of control span on control characteristics was obtained by testing the outboard one-third, outboard two-thirds, and the complete control. The complete control extended from 29 to 86% of the wing semi-span and was located between the 80- and 94%-chord lines. The unswept wing of the fighter-type aircraft had an aspect ratio of 2.42, a taper ratio of 0.433, and a modified NACA 654005 aerofoil section. Six-component force and moment data were obtained through an angle-of-attack range of approximately -6 to 16 deg. for Mach numbers from 0.60 to 1.20. The test Reynolds number varied from  $1.42 \times 10^6$  to  $1.90 \times 10^6$ .

VJB

AD 634562 DTMB Rep. 2201 Aero Rep. 1109 UNLIMITED

David W. Taylor Model Basin, Aerodynamics Lab.,  
Washington, D.C., U.S.A.

533.695.12  
533.6.011.55  
533.6.013.412

LONGITUDINAL AERODYNAMIC CHARACTERISTICS OF  
SEVERAL HYPERSONIC AIRCRAFT CONFIGURATIONS AT  
A MACH NUMBER OF 6.26

Krouse, J.R., E11s, B.K.

May, 1966 33pp., 8ref.

Wind tunnel tests were conducted at M=6.26 on configurations consisting of various half-cone-cylinder bodies and double-delta wings. Effects of body volume, vehicle orientation, wing planform, and wing-tip dihedral were determined. In general, the lift-to-drag ratios of all high-wing configurations varied slightly over an angle-of-attack range of 0 to 12deg., reaching maximum values of about 3.2 near 6 deg. The lift-to-drag ratios of all low-wing configurations increased continuously with increasing angle of attack, eventually reaching maximum values of about 3.6 near 10deg. In all cases, fuselage base drag accounted for less than 10% of the total drag. For the arbitrarily chosen centre-of-gravity location, all low-wing configurations were stable but unbalanced whereas several high-wing configurations were both stable and balanced.

ENR

P 146412 FWA FR 1669 NASA CR 54545  
N66-39939

UNLIMITED

United Aircraft Corp., Pratt & Whitney Air-  
craft Div., West Palm Beach, Fla., U.S.A.

533.695.5  
621.438.031  
621.438-253.5  
NAS 3-7603

SINGLE STAGE EXPERIMENTAL EVALUATION OF  
SLOTTED ROTOR AND STATOR BLADING. PART 2:  
ANNULAR CASCADE INVESTIGATION OF SLOT  
LOCATION AND GEOMETRY

31.10.1966 73pp., 87ref.

An annular cascade investigation was conducted to provide criteria for the design of slotted rotors and stators to be tested in a subsequent part of the overall programme. The test stators were 65-series aerofoils, having a chord length of 6.5 inches and a calculated midspan D-factor loading of 0.528 without slots. A slot located approximately midway between the point of minimum pressure and the point of separation produced the best performance, reducing the wake loss coefficient to about 17% of that for the unslotted vane and increasing the lift coefficient and air turning angle approximately 10% and 2 degrees, respectively.

VJB

P 146174	SID 65-1353	NASA CR 65329 N66-21562 FR	UNLIMITED
North American Aviation Inc., Space & Information Systems Div., Calif., U.S.A.			533.696.5 533.6.011((517.949.8))
STUDY OF FLOW FIELDS ABOUT AXISYMMETRIC BLUNT BODIES AT LARGE ANGLE-OF-ATTACK			681.3.06 N8 9-3159

Webb, H.O.  
29.10.1965 153pp., 23ref.  
Presents a detailed theoretical formulation of the solution of real gas inviscid flow fields about axisymmetric blunt bodies at large angles-of-attack, travelling at supersonic speeds. An IBM 7094 computer program has been developed to do the calculation. Also, given are sample results of two cases and an explanation of the numerical procedures used in the finite difference solution.

29F

NASA TM X-53156	N65-14934	UNLIMITED
National Aero & Space Admin., Washington, D.C.		
U.S.A.		533.697.3
A STUDY OF DENSITY VARIATIONS IN FREE MOLECULAR		533.6.011.6
FLOW THROUGH CYLINDRICAL DUCTS DUE TO		
ACCOMMODATION COEFFICIENTS		
Robertson, S.J.		

46pp..27ref.

Investigates theoretically free-molecule flow through a duct of circular cross-sections. The molecular flux to the duct wall and exit plane was calculated along with the total flow rate through the duct. The density field was calculated at the duct exit and along the centre line for various duct wall temperatures and thermal accommodation coefficients.

**RCF**

P 146556 DLR FB 67-04 , DVL Ber. 584 UNLIMITED  
Deutsche Versuchsanstalt für Luft- und  
Raumfahrt, Germany 533.697.4  
THEORETICAL AND EXPERIMENTAL ANALYSIS OF THE  
STATIC PRESSURE IN A PLANE TURBULENT JET AT  
LOW MACH-NUMBER (THEORETISCHE UND EXPERIMENTELLE  
ANALYSE DES STATISCHEN DRUCKES IM EBENEN  
TURBULENTEN FREISTRALH BEI KLEINER MACHZAHL)  
Report in German

Fiedler, H.  
Jan., 1967 11kop., 32raf.  
A turbulent jet is considered. Theoretical pressure distributions were obtained with the aid of the complete Reynolds equation. For the purpose of experimental investigation, the influence of the turbulence on the static pressure reading was determined by dynamic calibration of the probe. A combination probe, consisting of Pitot tube and hot wire, was also developed for measuring the static pressure in a turbulent stream. The experimental results were in good agreement with the theory. Generally it was found that in the turbulent region of the jet the static pressure is negative with respect to the pressure of the ambient still air.

P 146201	ARL 66-0160	UNLIMITED
Aerospace Res. Labs., Wright Patterson AFB, Ohio, U.S.A.		532.529.3 533.697.5
ANALYTICAL AND EXPERIMENTAL INVESTIGATION OF SUPERSONIC INJECTORS WITH LARGE SECONDARY MASS FLOWS		

Pinchak, A.C., Stephen, B.O.  
Aug., 1966 53pp., 5ref.  
The results presented are for air-air constant area supersonic injectors. Data were taken with secondary mass flows, both larger and smaller in magnitude than primary mass flow. Both air-air and mercury-helium injectors were treated in the calculations.

**HCF**



# PLASMA PHYSICS

21

P 146371

DLR-ForschBer., (FB 64-74), Germany

WORKING SHEETS FOR THE CALCULATION OF PLASMA

ACCELERATION IN CROSSED FIELDS

Stoffers, G.

June, 1966

30pp., 9ref.

UNLIMITED

533.951

518.3

For the plasma acceleration in crossed electromagnetic fields, the equation of motion is integrated for the case of constant flow area, constant electric field strength and constant magnetic induction, the flow being treated as a one-dimensional problem. From the integrated equation of motion, nomographs are derived for the graphical evaluation of the mutual relations between the velocity, the pressure, the electric field strength, the magnetic induction, and the employed electric work. The so-called velocity of momentum rate is used as an auxiliary quantity.

# ACOUSTICS & VIBRATIONS

AD 638134

NOL TR 66-146

UNLIMITED

Naval Ordnance Lab., White Oak, Md., U.S.A.

ACOUSTIC IMPEDANCE OF SEA WATER AS A FUNCTION OF

TEMPERATURE, PRESSURE AND SALINITY

Bradley, D.L., Wilson, W.D.

19.7.1966

14pp., 3ref.

551.48

534.231.3

The acoustic impedance (pc) of sea water is presented as a function of temperature, pressure and salinity. This acoustic impedance has been calculated from empirical equations developed at the Naval Ordnance Laboratory to represent the velocity of sound and density of sea water as functions of the parameters temperature, pressure, and salinity. Tables of the calculated data and graphs are given.

VJB

P 146110

UTIAS TR 110

UNLIMITED

Toronto Univ., Inst. for Aerospace Studies,

Canada

REFRACTION OF SOUND BY JET FLOW AND JET

TEMPERATURE, II

Grande, E.

51pp., 21ref.

532.525.2

534.25

APOSR 672-64

The refraction of the sound field of an omnidirectional pure tone 'point' source of sound by the temperature and velocity fields of a 3/4 in. air or nitrogen jet was measured. Several different sound source positions were employed; one within the potential core of the jet, others off the axis, entirely outside the jet.

VJB

AD 635849

FTD TT 65-1851

UNLIMITED

Foreign Tech. Div., Wright-Patterson AFB,

Ohio, U.S.A.

ON COGNITION OF SPEECH SOUNDS WITH THE AID

OF SELF-ORGANIZING SYSTEMS WITH TWO POSITIVE

FEEDBACKS (Transl. from: Avtomatika 2 (2),

59-70, 1964, U.S.S.R.)

Otkhmenuri, G.L.

25.5.1966

21pp., 4ref.

534.785

621-52

Discusses the use of self-organizing systems in the role of cognitive devices of second-degree speech. Shown are advantages of such systems in comparison with determinative systems. Block diagrams are proposed for the cognizance of sounds with the use of self-organizing systems. Given are methods of improving the cognizance part by the introduction of additional bonds. Also, given are certain experimental results with the use of self-organizing systems with one (basic) positive feedback.

VJB

P 146415 Rep.1272 NASA CR 74699 UNLIMITED  
 N66-21941  
 Bolt Beranek & Newman Inc., Cambridge, Mass., U.S.A. 534.836 ((629.757.45))  
 532.525.2  
 NAS1-4656  
 STUDIES OF THE NEAR-FIELD NOISE PROPERTIES OF A  
 SMALL AIR JET  
 Koest, D.N., Maldenik, G.  
 Feb., 1966 97pp.  
 The spectral and spatial-correlation properties of the noise field in the immediate vicinity of a small air jet have been recorded and analysed over the frequency range from 1000 Hz to 60,000 Hz.

VJB

#### OPTICS & INFRARED SYSTEMS

P 146350 FR AFRL 66-647 UNLIMITED  
 Idealab Inc., Franklin, Mass.; U.S.A. 535.411  
 MOBIUS BAND INTERFEROMETER  
 (20.5.1965 - 19.5.1966) AF 19(628)5184  
 Bullard, A.H.  
 15.8.1966 38pp., 1ref.  
 The procedure, techniques, and precautions observed in the design and construction of the Mobius Band Interferometer structure are discussed. Next, a review of the system design covering the servo configuration and the electronic sweep circuit is presented. The final section of the report covers in detail the operating controls and the procedure for component selection for variation of the sweep time and forward to flyback ratio. The auxiliary output features provided in the Idealab Interferometer Control Unit are described.

VJB

P 146349 Sci. Rep.3 AFRL 66-742 UNLIMITED  
 Brown Univ., Engineering Div., Providence, R.I., U.S.A. 535.421  
 SURFACE CURRENTS INDUCED ON WEDGES UNDER PLANE  
 WAVE ILLUMINATION AF 19(628)5846  
 Romano, R., Bolle, D.H.  
 Sept., 1966 33pp., 9ref.  
 Magnitudes and phases of the surface currents induced on perfectly conducting infinite wedges are presented as a function of the distance from the wedge apex. Results are presented for wedges with interior angles of 60, 90 and 120 deg. for various angles of incidence. Results are given for the polarization of the incident plane both in and normal to the plane of incidence.

VJB

#### HEAT, THERMODYNAMICS, COMBUSTION

RAE TR 66328 CPM 89 UNLIMITED  
 Royal Aircraft Est., Ministry of Aviation, U.K. 536.2.022  
 THE DETERMINATION OF THERMAL CONDUCTIVITY BY  
 MEANS OF MELTING PHENOMENA 536.421.1  
 Bishop, P.H.H., Rogers, F.F. 547.916  
 Oct., 1966 21pp., 3ref.  
 The property of melting is used to provide a cheap, quick and reasonably accurate determination of thermal conductivity, needing very little preparation of apparatus. The method is free from the need for constant ambient conditions, and can accommodate specimens of moderate flatness and any reasonable size and shape.

VJB

NASA TN X-55306 N66-37006 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 PROCEEDINGS OF CONFERENCE ON THERMAL  
 JOINT CONDUCTANCE 061.3 2.1964  
 19.2.1964 136pp. 536.21  
 621.08  
 Contains: Results of Contract NAS 9-5207 Thermal contact conductance in a  
 vacuum and related parameter study (Atkins, H.L.); Measurements of thermal  
 contact conductance in a vacuum (Kaspereck, W.E., Dally, R.M.); Thermal  
 joint conductance (Vickers, J.M.P.); Thermal conductance of molybdenum and  
 stainless steel interfaces in a vacuum environment (Somers, R.D., Coles W.D.)  
 VJB

NASA TN D-3741 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 A SURVEY OF THERMAL RADIATION STUDIES OF  
 ABLATING BODIES IN THE BALLISTIC RANGE 536.422.1  
 (PRESENTED AT THE THIRTEENTH NATIONAL 629.7.023.225  
 INFRARED INFORMATION SYMPOSIUM, OCT., 26-  
 28, 1965, IN PASADENA, CALIF.) 536.33  
 Fale, W.A.  
 Feb., 1967 19pp., 23ref.

Ames Research Centre has studied the radiative properties of the boundary  
 layer and near wake of ablating bodies flying in ballistic ranges. The  
 ablating materials investigated include polycarbonate, General Electric  
 124 resin, polyethylene, polyformaldehyde, Teflon, and cellulose nitrate.  
 Both absolute radiometric and spectrographic data were obtained. The  
 observed absolute amount of radiation varied greatly for the various mat-  
 erials. The chemical species responsible for the radiation in the spectral  
 range from 0.2 to 1.1  $\mu$  were CN, C<sub>2</sub>, NH, H, and solid carbon microparticles,  
 or soot. The results of the tests indicate a strong correlation between the  
 radiating species present and the carbon-oxygen ratio of the ablating  
 material.  
 HHC

P 146503 OFR 11 NASA CR 54405 UNLIMITED  
 N65-28625  
 General Electric Co., Missile & Space Div., 669.832  
 Cincinnati, Ohio, U.S.A. 536.423  
 ALKALI METALS BOILING AND CONDENSING 532.5  
 INVESTIGATIONS (1.1-31.3.1965) HAS 3-2520  
 Tippets, F.E., Converse, G.L. (Editors)  
 23.4.1965 67pp., 16ref.

Experimentation to determine two-phase heat transfer and fluid flow data  
 for potassium under conditions of boiling and condensing; approximating those  
 anticipated in large space turbo-electric power systems is reported for the  
 50 kW, 100kW, and 300kW facilities. The results for the 300 kW project show  
 the dependence of heat transfer performance on saturation temperature level,  
 tube exit quality, mass velocity and heat flux, the difference in performance  
 between co-current and counter-current flow, and the effect of the helical  
 insert compared to performance with a plain tube without insert.  
 CRH

P 146153 NBS 8750 N65-25244 UNLIMITED  
 NBSL CR 63149  
 National Bureau of Standards, Dept., 536.40  
 of Commerce, Boulder, Col., U.S.A. 536.532  
 AVAILABLE LOW TEMPERATURE THERMOCOUPLE 536.532  
 INFORMATION AND SERVICES Proj. 31503-12-3150532

Sparks, L.L., Powell, R.L.  
 15.2.1965 17pp., 2ref.  
 The Cryogenic Data Centre of the National Bureau of Standards maintains  
 "standard" tables of voltage vs. temperature for ten thermocouple pairs  
 frequently used at low temperatures. These tables contain interim values  
 which will be useful until national NBS, ASTM, and ISA tables are established  
 for cryogenic temperatures. The "standard" tables now available are slightly  
 different than the previously published tables. The differences are caused  
 by adjusting the older tables to obtain smoother first and second differences  
 of the voltages and sensitivities.  
 VJB

P 145197 Rep. 66510A FR N66-37905 UNLIMITED  
NASA CR 70446

Roscom Engineering Co.,  
Minneapolis, Minn., U.S.A.  
DEVELOPMENT OF A FAST RESPONSE TEMPERATURE  
GAUGE FOR ROCKET VEHICLE FLUING SYSTEMS  
(24.6.1964 - 24.6.1965)  
Stickney, T.H.  
10.6.1965 55pp., 14ref.

536.53  
629.7.063  
NBS 8-11629

Describes the development of a temperature gauge using a coaxial thermo-  
element, a platinum-rhodium multishield sensing head, and a one-piece  
superalloy mounting stem. The range of flow parameters and gas properties  
for which the temperature gauge was designed are noted, and the results of  
a materials survey and engineering analysis are presented. Proof test  
results are discussed and shown by graphical representations. Schematic  
diagrams and photographs of the gauge are included.

MHC

P 146144 FR 0700-1161 N66-31701 UNLIMITED  
NASA CR 76417

Aeromet-General Corp., Aerometrics,  
San Ramon, Calif., U.S.A.  
DEVICE FOR MEASURING THE TEMPERATURE OF LIQUID  
AND GASEOUS HYDROGEN  
Chandon, H.C., Larson, J.R.  
April, 1966 126pp.

661.96  
661.96-404  
536.53  
621.317.39(536)  
NBS 8-11362

A cryogenic temperature transducer was produced which is extremely fast in  
response to changing temperatures, is of medium accuracy and measures  
temperature over a wide range. The transducer will respond to a temperature  
change from -146 to -196 deg.C in 0.1 second. The range of the transducer is  
designed for -253 to +60 deg.C.

MHC

#### NUCLEAR, ATOMIC & MOLECULAR PHYSICS

NASA TR D-3540 UNLIMITED

National Aero. & Space Admin.,  
Washington, D.C.  
INVESTIGATION OF THE (d,  $\alpha$ ) REACTION ON  
ALUMINUM 27  
Priest, J.R., Vincent, J.S.  
Feb., 1967 17p., 16ref.

539.128.2:  
539.128.4  
669.71

The angular distributions of seven alpha-particle groups from the (d,  $\alpha$ )  
reaction on aluminium 27 ( $^{27}\text{Al}$ ) were measured. The deuteron energy was  
20.9 MeV in the laboratory system. The angular distributions are all  
peaked in the forward direction and have little structure. The integrated  
differential cross sections for those reactions that leave the  $\text{Mg}^{25}$  nucleus  
in the  $K = 5/2^+$  rotational states are, in general, more than one order of  
magnitude larger than those that leave  $\text{Mg}^{25}$  in the  $K = 1/2^+$  rotational  
states. The angular distributions corresponding to a given rotational band  
in  $\text{Mg}^{25}$  are strikingly similar both in magnitude and shape.

VJB

P 146206 FR ARL-66-0130 UNLIMITED

Brunel Univ., Uxbridge, Middx., U.S.A.  
ELECTRON PARAMAGNETIC RESONANCE AND  
OPTICAL STUDIES OF IMPURITY IONS IN SINGLE  
CRYSTAL HOSTS (15.4.1963 - 15.4.1966)  
Dorian, P.B.  
July, 1966 108pp., 40ref.

539.194(533.22)  
535.333  
U-10073:1051  
AF 33(657)-11104

The electron paramagnetic resonance and optical spectra of several systems  
is reported. These systems are  $\text{Re}^{+4}$  in  $\text{K}_2\text{PtCl}_6$  single crystals and  $\text{V}^{+4}$  and  
 $\text{Mn}^{+4}$  in  $\text{SnO}_2$  single crystals and S.O. gas.

D.L.

NASA TN D-3351

UNLIMITED

National Aero. & Space Admin., U.S.A.  
CALCULATION OF THE CENTERED ONE-DIMENSIONAL  
UNSTEADY EXPANSION OF A REACTING GAS MIXTURE  
SUBJECT TO VIBRATIONAL AND CHEMICAL NONE-  
EQUILIBRIUM

539.194  
533.1

Conner, L.H.

Feb., 1967 42pp., 23ref.

A method of calculation based on a previously developed method-of-characteristics approach is presented for use in analyzing the non-equilibrium one-dimensional unsteady expansion of a reacting mixture of gases. The characteristic equations are written in a general form which permits the consideration of a number of rate processes. A multi-component gas model with a number of simultaneous rate processes is used, and both chemical and vibrational non-equilibrium are permitted. A procedure which utilizes the method of characteristics in a Lagrangian frame of reference is programmed to yield solutions on the IBM 7094 electronic data processing system. Calculations are presented for a typical unsteady expansion to demonstrate the use of the program.

MHC

P 146156 WIS TCI 100 N66-29380

UNLIMITED

Wisconsin Univ., Theoretical Chemistry Inst.,  
& Chemistry Dept., Madison, U.S.A.

539.198

THE EXTREME-EFFECT IN TOTAL ELASTIC MOLECULAR  
BEAM SCATTERING CROSS SECTIONS FOR  
CHARACTERIZATION OF THE POTENTIAL WELL.

Grant NoG 275-62

Bernstein, R.B., O'Brien, T.J.B.

14-16, 9.1965 24pp., 17ref.

The theory of the extreme-effect in elastic impact spectra is reviewed and extended. It has been shown previously that for any realistic inter-particle potential (whose well has a capacity for one or more bound states), extrema in the total elastic molecular beam scattering cross sections are expected at certain characteristic velocities. The limiting high-velocity spacing of successive extrema on a  $1/v$  plot is found to be inversely proportional to the product of the well depth times the inter-particle separation  $r_m$  at the potential minimum. It is shown that the constant of proportionality is closely related to the curvature of the well and thus to the force constant of the di-atom (or "complex" molecule). Methods are discussed for the extraction of the maximum amount of information on the shape of the potential well from measurements of the extreme-effect.

FHM

# CHEMISTRY

NASA TR R-254

UNLIMITED

National Aero. & Space Admin., U.S.A.

KINETIC THEORY OF BIMOLECULAR CHEMICAL  
REACTION, DIFFUSIVE DRAG, AND OTHER PROCESSES  
IN A GAS MIXTURE

533.1

533.7

Hord, R.A.

541.12

Feb., 1967 42pp., 14ref.

For two gas species with a temperature difference and a bulk velocity difference neither of which is necessarily small in magnitude, the kinetic theory of gases has been used to derive explicit expressions for the collision frequency, diffusive drag force, molecular translational energy transfer rate, and the bimolecular chemical reaction frequency. The derivations, which are based upon hypothesized mutual collision diameters, activation energies, and steric factors, are of interest in connection with theoretical studies of low-pressure gas mixtures with large departures from equilibrium. A binary temperature concept is introduced as an aid in condensing and interpreting the expressions derived from the kinetic theory. The expression derived for the diffusive drag force is used to give a more definite form to the equations of motion of the individual species in a mixture of several interdiffusing gases.

MHC

RAE TR 66340

CPM 92

UNLIMITED

Royal Aircraft Est., Ministry of  
Aviation, U.K.

543.257.1

THE POTENTIOMETRIC DETERMINATION OF  
FLUORIDE WITH LANTHANUM NITRATE AND ITS  
APPLICATION TO THE MICRO-DETERMINATION OF  
FLUORINE IN ORGANIC COMPOUNDS

546.101

543.063

Cheesman, D.F., Webb, J.R.

Oct., 1966 13pp., 4ref.

The unbuffered fluoride solution is adjusted to pH 6.3 and titrated with 0.05N lanthanum nitrate solution. A rapid decrease in pH at the end-point, due to hydrolysis of the excess of lanthanum ions, is followed with a quinhydrone indicator/calomel reference electrode system. Sulphate, phosphate, carbonate and silicate ions interfere. Methods for removal of all but the first of these are described. The method has been applied to the determination of fluorine in organic compounds. Results were within 0.5% absolute.

P 146343 AFRL 66-652 PERM 267 UNLIMITED  
 Air Force Cambridge Res. Labs.,  
 Hanscom Field, Mass., U.S.A. 546.273  
 A STUDY OF BORON HALIDE - GROUP V 546.851  
 HALIDE COMPLEXES  
 Arrington, A.F., Weiner, J.R., et al.  
 Sept., 1966 10pp., 10ref.

Attempts were made to produce Lewis acid complexes of boron triiodide, tri-bromide and trichloride with the triiodides, tribromides and trichlorides of phosphorus, arsenic and antimony. The experimental method used involved the combining of the reagents in carbon disulphide at reduced temperatures. Of the 27 possible complexes, only 6 were formed. Of these only 4 complexes are stable. These are boron triiodide-phosphorus triiodide, boron triiodide-phosphorus bromide, boron-tribromide-phosphorus triiodide and boron tri-bromide-phosphorus triiodide and boron tribromide-phosphorus bromide. Boron triiodide-phosphorus trichloride and boron tribromide-phosphorus trichloride formed, were not stable, however, and did undergo cross halogenation and decomposition. Results of this are compared with other studies for these compounds which have been prepared in the literature. Some properties of the stable complexes are evaluated qualitatively. FIM

NASA TR R-253 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 COUPLED VIBRATION AND DISSOCIATION RELAXATION 546.264-31  
 BEHIND STRONG SHOCK WAVES IN CARBON DIOXIDE 533.6.011.72  
 Hindelang, F.J. 539.194  
 Feb., 1967 34pp., 20ref.

The harmonic oscillator rigid-rotator model has been used to calculate the relaxation region behind a shock wave in carbon dioxide. Finite relaxation rates for the 3 different vibrational modes and 2 dissociation reactions are included. Models for the coupling between the vibrational relaxation and the dissociation process are based on the assumption that dissociation can proceed from any vibrational level with equal probability. Two different models for the vibrational excitation have been examined. Solutions have been obtained for the interdependent fluid flow, chemical rate, and vibrational relaxation-rate equations incorporating estimated rate coefficients. Results are presented in the form of flow-field profiles for density, pressure, translational and vibrational temperatures, and species concentrations. The effects of vibrational excitation, vibration-dissociation coupling, and energy exchange between the vibrational modes are investigated. The effect of vibrational relaxation and vibration-dissociation coupling is much stronger in CO<sub>2</sub> with three different vibrational modes than in diatomic gases with only a single mode. FIM

#### INSTRUMENTATION

AD 636940 E 1730 MDC TR 66-66 UNLIMITED  
 Massachusetts Inst. of Tech.,  
 Instrumentation Lab., Cambridge, U.S.A. 53.032.16  
 GYRO TEST STATION CHECKOUT AND EVALUATION 620.1.05  
 Giannoukos, W.J. AF 29(500) 5470  
 April, 1966 50pp., 10ref.

A theoretical discussion of the procedures utilized to check out a gyro test station is presented. An analysis of test results which permits evaluation of the test station is described. The study also includes a brief description of the components involved and the techniques of testing as performed by the Massachusetts Institute of Technology, Instrumentation Laboratory.

VJB

NASA MISC 297 N66-32057 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 A LINEARIZED ANALYSIS AND DESIGN OF AN 531.31  
 AUTOMATIC BALANCING SYSTEM FOR THE THREE-AXIS 621-52  
 AIR BEARING TABLE 621.022-85  
 Zajac, F., Smell, D.  
 10pp.

Presents the analysis and design of an automatic control system to reduce the mass unbalance to 5000 dyne-cms or less. To balance the table (eliminate the static mass unbalance) about three axes, the table is first balanced manually to within 200,000 dyne-cms of torque balance in the horizontal position. After this balancing the table should be pendulous, but with a period greater than 2.0 minutes. The table is then released from an appropriate initial position, and the automatic balancing system is activated. This system senses a positional error from the initial position, resulting from a torque unbalance, and corrects this unbalance by driving a weight along the appropriate axis.

RLE TR 66352

IR 79

UNLIMITED

Royal Aircraft Est., Ministry of  
Aviation, U.K.

531.767.9

A SEMI-AUTOMATIC EQUIPMENT FOR THE  
CALIBRATION OF PRESSURE TRANSDUCERS

Pole-Daker, P.C.

Nov., 1966

21pp., 1ref.

An equipment for the calibration of pressure transducers by a continuous sweep method is described which enables transducers having range maxima between 0.5 and 5000 lb/in<sup>2</sup> to be calibrated with an overall accuracy better than 0.1% of full scale. The system is shown to have certain advantages over the conventional point-by-point methods of calibration.

VJD

P 146177

NASA CR 74474.

UNLIMITED

N56-29457

Research Triangle Inst., Durham, N.C., U.S.A.  
SILICON NEEDLE TRANSDUCER

621.302

531.767.9

Stockard, R.R., Wortman, J.J.

061.3 \*1966

1966

6pp., 4ref.

537.220.1

N5R 222

Paper presented at the 1966 International Solid-State Circuits Conference, Philadelphia, Pa. Basically the silicon needle is a transducer of force and displacement. Its practical usefulness has been demonstrated by incorporating it into a laboratory accelerometer. The advantages of this transducer using the p-n junction effect include the elimination of critical alignment problems and the fact that it can be made more sensitive to stress.

VJB

P 146501

NL 7002-1

NASA CR 69543

UNLIMITED

N66-15764

Metrophysics Inc., Santa Barbara,  
Calif., U.S.A.

531.767.9

681.341.32

ADVANCED TRANSDUCERS PHASE A: INVESTIGATION  
OF DIGITAL TRANSDUCERS AND DIGITAL COMPATIBILITY  
TECHNIQUE

N53 3-20515

Nov., 1965

200pp., 125ref.

This phase includes the following tasks: (1) Surveys present transducer and signal conditioning designs and automatic checkout techniques, with particular emphasis on digital compatibility. (2) Investigates conditioning and digital conversion requirements for both high-level (0-5 volt) and low-level (millivolt) output signals. (3) Investigates transducer "add-on" modules. (4) Studies long-term design approaches for physically integrating sensors and modules into new configurations.

VJB

NASA TN D-3811

UNLIMITED

National Aero. & Space Admin., U.S.A.  
VARIATIONS IN GAGE CONSTANT AS A FUNCTION  
OF EMISSION CURRENT IN AN UNSHIELDED OPEN-  
END GRID BAYARD-ALPERT IONIZATION GAGE

531.768.7

Melfi, L.T., Kern, P.J.

Feb., 1967

19pp., 9ref.

A detailed laboratory study has revealed a gauge-constant-emission-current anomaly in the 1- to 10-milliamper emission-current range in an open-end Grid Bayard-Alpert ionization gauge. This study was performed for the pressure range from  $6 \times 10^{-2}$  to  $1 \times 10^{-5}$  N/m<sup>2</sup> on an orifice-conductance calibration system with a computed pressure measurement uncertainty of 5%.

VJB

# COMMUNICATION THEORY

AD 638449	P-3441	UNLIMITED
Rand Corp., Santa Monica, Calif., U.S.A.		
INFORMATION THEORY AND ALTERNATE		519.54
HYPOTHESIS TESTS		521.391
Bussgang, J.J., Marcus, H.P.		
Sept., 1966	34pp., 6ref.	

Lindley's (1956) concept of the information in an experiment is used to study alternate hypothesis statistical tests. A test is considered to be a combination of a sampling rule and a decision rule which is based on the samples taken. An information theoretic analysis of alternate hypothesis tests is developed. Using this approach new results on SPRT's and alternate hypothesis tests in general are obtained.

VJB

# ELECTRICITY AND MAGNETISM

P 146199	ARL 66-0107	UNLIMITED
Aerospace Res. Labs., Wright Patterson AFB,		
Ohio, U.S.A.		537.523.3
THE EFFECTS OF PARTIAL CONDENSATION AROUND		
IONS IN ELECTRIC FLUID DYNAMIC ENERGY CON-		
VERSION PROCESSES (OCT. 1963-MARCH 1964)		
Decaire, J.J.		
Sept., 1966	51pp., 34ref.	

Fluid dynamic energy is converted directly into electrical energy - unipolar charges are seeded into a gas flow and are transported by viscous interaction with the gas molecules to an electrode of high potential. The effectiveness of the viscous coupling depends on the charge mobility being greatly increased when colloid sized particles rather than molecular ions are used as the charge carriers. The mobility of charged colloids is discussed theoretically.

VJB

P 146200	ARL 66-0104	UNLIMITED
Aerospace Res. Labs., Wright Patterson AFB,		
Ohio, U.S.A.		533.95
SURVEY OF INVESTIGATIONS OF ELECTRIC ARC		
INTERACTIONS WITH MAGNETIC AND AERODYNAMIC		
FIELDS		
Myers, T.W., Roman, W.C.		
Sept., 1966	115pp., 167ref.	538.4

Summarizes and evaluates the existing literature related to the interaction of an electric arc at pressure levels of one atmosphere or greater with magnetic fields and/or aerodynamic fields which are transverse to the arc column. The scope of this survey does not include the subject of retrograde motion. For the purposes of this survey, the subject is broken up accordingly to whether or not there is net arc motion with respect to the electrodes. When motion occurs, the arc is designated a travelling arc; this is the type of arc which occurs in rail acceleration, arc heaters utilizing magnetically rotated arcs and electric switchgear circuit breakers. When the arc undergoes no net motion with respect to the electrodes it is designated a stationary arc; this type occurs when the arc is balanced in a transverse gas flow by an appropriate transverse magnetic field. VJB

P 146202	ARL 66-0191	UNLIMITED
Aerospace Res. Labs., Wright Patterson AFB,		
Ohio, U.S.A.		533.95
INVESTIGATION OF ELECTRIC ARC INTERACTION		
WITH AERODYNAMIC AND MAGNETIC FIELDS		
Roman, W.C., Myers, T.W.		
Oct., 1966	59pp., 16ref.	538.4

An experimental study of a balanced electric arc of 200 to 400 amperes in an atmospheric pressure cross-flow air stream of velocities up to 60 ft/sec and transverse magnetic field strengths up to 50 gauss was made. An open jet type facility permitted the use of diagnostic techniques in the arc wake region. The arc's significant dimension transverse and parallel to the flow was measured. This dimension increased transverse to the flow and decreased parallel to the flow as the transverse blowing velocity was increased. Velocity profiles, energy flux distributions, relative turbulence levels and frequency measurements were obtained in the arc wake using miniaturized probe techniques. Flow visualization studies were performed using micron-sized particles. The input and output arc power distribution was obtained.



# ELECTROMAGNETIC PROPAGATION

29

AD 6393M IEL Rep.1379 UNLIMITED  
 Navy Electronics Lab., San Diego, Calif.,  
 U.S.A. 621,3,013  
 ELF SURFACE ELECTRIC AND MAGNETIC FIELDS AND 621,319.7  
 UNDER-WATER ELECTRIC FIELDS, SPECTRAL 538,562.2  
 ESTIMATES OF FIELDS IN 4-25-C/S RANGE BASED U 1086:1226  
 ON SURFACE MEASUREMENTS AT BORDER FIELD AND  
 UNDERWATER MEASUREMENTS AT 1000 FEET  
 Hughes, H.O.  
 27.5.1966 19pp.

Investigations into the electromagnetic environmental characteristics of the deep ocean in which present and future submarine communication systems must operate were conducted. (1) Surface measurements were made, consisting of simultaneous observations of the fluctuations in the vertical electric field and in the north-south magnetic field at IEL's Border Field Station. (2) Underwater horizontal electric-field fluctuations were recorded by measuring the voltage between probes on a boom mounted on the exterior of the Cousteau diving saucer. (3) Spectral analysis of the recordings was accomplished by computer and is presented in this report. (4) Significant peaks were found to occur in the underwater spectra in the region of the first resonant frequency of the earth-ionosphere cavity between 7 and 10 Hz.

## ELECTRICAL ENGINEERING - GENERAL

P 146225 FR NASA CR 65411 UNLIMITED  
 N66-30790  
 Union Carbide Corp., Carbon Products Div., 621,3,036.61  
 Ohio, U.S.A. 546.26  
 CARBON ELECTRODE DEVELOPMENT PROGRAM NLS 9-3699  
 (3.11.1964 - 3.5.1965)  
 24.5.1965 44pp.

Results are presented of a study conducted to improve 16 mm. solar positive carbon electrodes. Principal improvements sought were stronger more reliable carbon joints and the elimination or minimization of arc sputtering. The development work on the electrode joints is summarized. The study of core formulations is discussed. The manufacture of a limited production run of carbon electrodes having the most improved composition is described. A process flow diagram showing the manufacturing operations involved in making solar arc carbons is included.

MHC

AD 636193 TM 1 UNLIMITED  
 Naval Applied Science Lab.,  
 Brooklyn, N.Y., U.S.A. 621,3,066.6  
 INVESTIGATION OF PLATINGS OF ELECTRICAL 609,056.9:  
 CONTACTS 537,311.4  
 3.7.1966 31pp, 5ref.

MIL-C-26636 size no. 16 and no. 20 pin and socket contacts were electroplated with gold over silver, gold over nickel, gold over copper, rhodium over nickel, and rhodium over silver. Plated contacts were wired and assembled in a modified louvred Stevenson Screen and installed at the NASL environmental site at Ft. Tilden, N.Y. mounted on a supporting structure facing the ocean without obstruction, approximately 500 feet from the shore line and 40 feet above M.L.W. Contact resistance measurements on contacts mated 100 times as compared to contacts mated once, prior to exposure, show no significant difference except for a 30% increase for those plated with rhodium over nickel.

GTH

USNR Rep. 66/30 UNLIMITED  
 U.K. Scientific Mission, Washington, D.C.  
 1966 POWER SOURCES CONFERENCE. PART III: 061,3 May 1966  
 POWER CONDITIONING 621,311.69  
 Griffiths, D.L. 621,314.5  
 Dec., 1966 5pp. U 0519:10379:10372  
 Topics discussed include modulation systems, current-fed and static inverters, manual generators and devices to protect solid-state electronics from surge energy.

PBP

P 146176 QRO WOD 30531 UNLIMITED  
 Westinghouse Defense & Space Center,  
 Surface Div., Baltimore, Md., U.S.A. 621.38.004.6  
 RESEARCH ON FAILURE FREE SYSTEMS U 1613  
 (23.3 - 23.6.1966) NLSW 572  
 1966 8pp., 1ref.

Research is being conducted to develop new techniques for increasing the reliability of vital electronic systems. The status and technical activities performed during this period on the current phase of the program are described. This phase provides for the documentation of a computer simulation program to perform reliability analyses of a wide variety of failure responsive redundant systems, and the development of computerized procedures for efficiently allocating a limited number of tests points within a redundant system and for estimating the system reliability when one or more components may have failed at the time of estimation.

PDP

#### ELECTRICAL POWER (INCLUDES BATTERIES & FUEL CELLS)

P 146413 FR NAS: CR 69804 UNLIMITED  
 N66-16190  
 Radiation Applications Inc., L.I., 621.352.1  
 New York, U.S.A. 670.742.2  
 FABRICATION AND TEST OF BATTERY SEPARATOR NAS 7-100  
 MATERIALS RESISTANT TO THERMAL STERILIZATION  
 Wetherell, T.J., Searchville, P.A.  
 Dec., 1965 269pp.

Fifty-one materials were fabricated, using polyethylene as the base polymer, by crosslinking and grafting procedures. Each material was tested for its ability to withstand heat sterilization and to function as a battery separator in the silver-zinc alkaline system. Cells, constructed from seven materials which successfully withstood heat sterilization, retained greater than 9% of electrical capacity of control cells during five deep cycles of charge and discharge. The two materials described below are selected to be produced in 500 ft.<sup>2</sup> quantities, which are to be used for further testing.

VIB

P 146160 EOS 4110 ML 20 N66-29761 UNLIMITED  
 NAS: CR 76031  
 Electro-Optical Systems Inc., 621.352.6  
 Pasadena, Calif., U.S.A. NLS 3-2781  
 HYDROGEN-OXYGEN ELECTROLYTIC REGENERATIVE  
 FUEL CELLS (1.7-1.8.1965)  
 Klein, M.  
 10.9.1965 14pp4

Single cells with various electrode structures were tested to obtain a better understanding of cell performance controlling factors, and methods of improving the oxygen electrode. The first 500 watt, 3/4 series cell prototype was assembled and subjected to preliminary tests. It incorporated new insulators fabricated from glass epoxy sheet and platinized porous nickel plaque electrodes of the standard EOC type.

EHR

#### SEMI-CONDUCTORS, TRANSISTORS

P 146206 FR ARL 66-0071 UNLIMITED  
 Marquette Univ., Milwaukee, 548.52  
 Wisconsin, U.S.A. 621.315.612  
 RESEARCH ON DEFECT CONTROLLED ELECTRICAL U 1044.103152  
 PROPERTIES OF RUTILE AF 33(615)-1244  
 Hirthe, W.H.  
 April, 1966 00pp., 22ref.

The electrical conductivity of single crystals of rutile was measured in the "C" direction over the temperature range 800 deg.C. to 1500 deg.C. and from 1 to 10-15 atm. of oxygen. The electrical conductivity of rutile in air below approximately 950 deg.C. appears, on the basis of this investigation to be impurity controlled due to the presence of aluminum rather than intrinsic conduction.

DMA

AD 635626 RAD Crane Rep. Note Issue UNLIMITED  
 66-264 16  
 Naval Ammunition Depot, Crane, Ind., U.S.A. 621.38.049.7 (S.I.C.)  
 INFORMATION ON MICROELECTRONICS FOR NAVY U 156772:1691  
 EQUIPMENTS

1.4.1966 53pp.  
 The test data contained in this issue of  $\mu$ -NOTES is data taken on units which were removed from life test. The life tests were conducted at 25 deg.C ambient temperature with nominal power supply voltage applied to the units while operating in ring counter configurations.

DMA

P 146350 AFRL 66-641 FSRP 266 UNLIMITED  
 Air Force Cambridge Res. Labs.,  
 Hanscom Field, Mass., U.S.A. 540.52  
 SOME FACTORS AFFECTING THE GROWTH OF BETA SILICON CARBIDE 540.201:251  
 621.38.049.7 (S.I.C.)  
 Ryan, C.E., Berman, I., et al. U 1044:156713  
 17pp., 10ref.

Discusses the growth of beta silicon carbide by the hydrogen reduction of methyl trichlorine onto carbon substrates at 1500 deg.C. It is shown that alpha inclusions present are the rare 2H (Wurtzite) modification of silicon carbide and that their presence resulted from a vapour-liquid-solid growth mechanism which was dominated by impurities in the substrate. By carefully cleaning the substrate and purifying the methyltrichlorosilane, the alpha inclusions were eliminated. The 2H alpha crystals were then deliberately grown by introducing selected impurities locally on the substrate. Beta crystals were also intentionally grown by the vapour-liquid-solid technique by introducing appropriate impurities. Growth of beta silicon carbide from the melt is also briefly discussed.

PDP

P 146137 AFRL 66-750 IP 121 UNLIMITED  
 Air Force Cambridge Res. Labs.,  
 Bedford, Mass., U.S.A. 537.312.621  
 TECHNIQUE FOR FABRICATION OF  $Al-Al_2O_3-Pb$  621.302.231  
 SUPERCONDUCTING TUNNEL DIODES 546.621:21:015  
 Silva, H.J. U 1004:156722  
 Nov., 1966 9pp., 6ref. Proj. 8603

This report describes an improved method of growing  $Al-Al_2O_3-Pb$  superconducting tunnel diodes. Since the resistance of the diode is dependent upon the thickness of the oxide layer, this layer must be carefully controlled in order to fabricate diodes of the desired resistance in a reproducible manner. The key to this method is a substrate holder which allows the entire process to be completed under vacuum.

DMA

AD 629206 QPR 3 UNLIMITED  
 Fairchild Engine & Airplane Corp.,  
 Fairchild Semi-Conductor Div., U.S.A. 650.51  
 PRODUCTION ENGINEERING MEASURE FOR IMPROVEMENT 621.302.332  
 OF PRODUCTION TECHNIQUE TO INCREASE THE U 171:1617:156760  
 RELIABILITY FOR PNP INTERMEDIATE POWER DI. 36-039 AMC 06155(E)  
 SILICON FLINGER SWITCHING TRANSISTORS  
 INCLUDING 2N3502 (1.7. - 30.9.1965)  
 McKeown, W., Walker, H.  
 27pp.

AD 630835      FR 66-17-105      TR Rep.1      UNLIMITED  
                                          TR EQOM  
                                          01541-1      621.302.333;  
                                               539.1.044  
                                               U 156767:10051;  
                                               DA-28-043-JTC-01541(E)

Hughes Aircraft Co., Fullerton,  
 Calif., U.S.A.  
 EFFECT OF TRANSISTOR DESIGN PARAMETERS ON  
 RADIATION RESISTANCE (POWER TRANSISTORS)  
 (1.7 - 30.9.1965)

Honnold, V.R., Thomas, G.D., et al.  
 March, 1966      15pp., 11ref.

Work carried out consists of the formulation of physical design theory including the effects of injection level. In addition, the sequencing of the fabrication steps for the 212369 is laid out in accordance with statistical design principles, and transistor fabrication initiated. Instrumentation design is completed and construction started on the circuits.

DMA

#### ELECTRICAL TESTING & INSTRUMENTS

NASA TR X-53425      N66-31231      UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 THE DESIGN AND DEVELOPMENT OF A DYNAMIC  
 BRUSH WEAR MEASUREMENT APPARATUS  
 Horton, J.C., Owens, J.E.  
 8.4.1966      25pp., 6ref.

An apparatus that permits the continual measurement of electrical brush wear in high vacuum is described. A linear voltage differential transformer is used as the sensing element and its output is displayed on a potentiometric recorder. Resolution may be obtained from 0.0001 inch to 0.025 inch total wear, thus permitting wear rate measurements from  $10^{-7}$  inches/hour to one inch per hour to be made. Calibration curves are shown, and the results from several tests are plotted and analyzed. Accuracy is shown to be better than  $\pm 0.5\%$ .

VJB

P 146235      TR 66-3-N      N66-27231      UNLIMITED  
 G.C.A. Corp., Tech. Div., Bedford,  
 Mass., U.S.A.  
 DEVELOPMENT OF A MASS SPECTROMETER EMPLOYING  
 A PHOTOIONIZATION SOURCE  
 Poschenrieder, W.P., Barrington, A.F.  
 Feb., 1966      57pp., 23ref.

Deals with the construction of a mass spectrometer that uses photoionization for the ion product. By the use of uv light and in particular with a uv vacuum monochromator to select the proper wavelength, simplified spectra generally are achieved, since in contrast to the commonly used electron impact ion source fragmentation of molecules can be suppressed. Additional advantages are the exclusion of chemical reactions with hot filaments and the elimination of outgassing from heated elements that are present in electron impact ion sources.

VJB

P 146272      FR      N66-39938      UNLIMITED  
                                          NASA CR 66201  
 National Res. Corp., Cambridge,  
 Mass., U.S.A.  
 DEVELOPMENT OF A MASS SPECTROMETER DESIGN  
 (1.6 - 31.12.1964)  
 Blum, P., Torney, F.L.  
 23.3.1965      60pp., 14ref.

Covers the second phase of a four phase programme to develop a cold cathode ion source mated to a quadrupole mass spectrometer. The completed unit is to be used as a residual gas analyzer. The cold cathode (magnetron) ion source was chosen because of lower background noise and higher sensitivities than the usual hot-filament types. This report describes the design of the ion source and the mass spectrometer and gives details of the construction and experiments with the ion source.

VJB

AD 624244 EES Rep. EES Rep. UNLIMITED  
 4E(1)66904 4E(1)66918  
 Naval Engineering Experiment Station, 621.318.4  
 Annapolis, Md., U.S.A. 530.22  
 U 10035:1006

**MAGNETIC CHARACTERISTICS OF "NON-MAGNETIC"  
 METALLIC MATERIALS, PERMEABILITY AND COERCIVE  
 FORCE IN STRONG FIELDS 100-200 OERSTEDS**

Gross, H.R., Ellinghausen, H.C.  
 6.4.1951 23pp., 10ref.

Contains data on a wide variety of materials such as brasses, bronzes, copper-nickel alloys, nickel base alloys, wrought and cast austenitic stainless steels, austenitic stainless steel weld metals, and austenitic manganese steels. Calculations include chemical composition, mechanical properties, normal permeability, coercive force and resistivity data for the materials tested. The permeability and coercive force measurements were performed in strong magnetic field (100-200 oersteds). The effect of composition and cold deformation on the magnetic properties of the various materials is discussed and considerable attention is focused on the austenitic stainless steels. In addition to general conclusions, the report contains generalizations as to the expected magnetic behaviour of the various types of materials.

DMA

AD 632340 TR ECOM 2672 UNLIMITED  
 Army Electronics Res. & Dev. Lab., 620.165  
 Fort Monmouth, N.J., U.S.A. 621.318.56  
 LIFE EXPECTANCY OF A NEW MINIATURE 5  
 POWER RELAY U 1016:103164  
 Fontana, W.J.  
 March, 1963 47pp., 14ref.

In a laboratory study a new miniature power relay design was subjected to a series of life tests to develop its life expectancy profile under a broad range of electrical operating conditions. The principle of factorial experimentation was applied to develop a test programme which, over the relay's design range of resistive load conditions, operating temperatures, and operating rates, would provide useful data at minimum cost. From the resulting statistical analysis, a series of functional relationships between the relay life expectancy and the operating stress levels were developed. Mathematical and graphical representations of these relationships are given.

DMA

**THEMO-6 PHOTO ELECTRICITY**

NASA TN D-3049 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 MECHANISM OF CADMIUM SULPHIDE FILM CELL 621.352.1:539.23  
 Fetter, A.E.Jr., Schalla, R.L. 546.322.21  
 Feb., 1967 12pp., 13ref. U 10321:156716

The cadmium sulphide film cell is a barrier-layer cell formed by a surface layer of chalcocite (Cu<sub>2</sub>S) on cadmium sulphide (CdS). The chalcocite is a very degenerate p-type semiconductor with the Fermi level 1 to 3 electron volts below the valence band edge. The barrier height of the junction is about 0.85 electron volt. The spectral response of the cell in monochromatic light for photon energies greater than 2.4 electron volts (the blue response) is ascribed to direct excitation across the band gap of cadmium sulphide plus photoelectric emission from the barrier layer. The response for photon energies less than 2.4 electron volts (the red response) is ascribed solely to photoelectric emission from the chalcocite layer. The efficiency of this process is greatly affected by surface damage and surface impurities. After heat treatment, the spectral response can be altered by illuminating the cell with constant-intensity blue or red light during the spectral-response measurements. (This is not the case before heat treatment). This effect is ascribed to impurities in the cadmium sulphide introduced from the copper sulphide layer by the heat treatment.

PP

P 146190 FR NASA CR 54959 UNLIMITED  
 N66-27741  
 Radio Corp. of America, RCA Labs., 621.383(523.72)  
 Princeton, N.J., U.S.A. 629.7.064.56  
 MATERIALS AND METHODS FOR LARGE-AREA SOLAR 5  
 CELLS (17.121.1964-16.12.1965) N13 3-6456  
 Ellis, S.G., Yohl, P., et al.  
 14.1.1966 25pp., 3ref.

GaAs/InAs/Al foil structures have been grown by oxide transport from the respective compounds. Preliminary studies have been made of the growth from the metallic elements using both halide transport and oxide transport. These latter methods have not yet been perfected. The light transmission of some cuprous selenide films on glass has dropped after a period of several months.

VJB

NASA TN D-3700

UNLIMITED

National Aero. & Space Admin., U.S.A.  
COMPARISON OF SOLAR DIRECT-ENERGY CONVERSION  
SYSTEMS OPERATING BETWEEN 1.0 AND 0.1  
ASTRONOMICAL UNIT

629.7.064.56

Zifano, W.J., Scudder, L.K.  
Feb., 1967 30pp., 7ref.

Three solar direct-energy conversion systems for operation in the 1.0 to 0.1 AU range were compared: thermoelectric flat plates (employing either lead telluride or silicon-germanium semiconductors), thermionic systems (including the solar concentrator), and uncooled silicon solar cells. Systems specific weight and power output variation during flight were used as a basis of comparison by assuming that an output power of 200 watts was required at the design point. Tilting the thermoelectric and solar cell panels from 0 deg. (panel normal to the incident radiation) to 90 deg. was assumed a means of solar flux control; however, no solar flux control was assumed for the thermionic systems.

VJB

LINES, NETWORKS, FILTERS & WAVEGUIDES

P 146361 AFRL 66-733 PSRP 202

UNLIMITED

Air Force Cambridge Res. Labs.,  
Hanscom Field, Mass., U.S.A.

621.372.54

OPTIMUM DESIGN OF SYMMETRICAL PARALLEL-T  
R-C NETWORKS

U 12371

Purnhagen, T.G.

Oct., 1966

11pp., 5ref.

Presents the information necessary for the design of symmetrical parallel-T R-C networks with symmetrical frequency response such that the networks will have optimum characteristics subject to certain circuit or performance constraints. Three cases are considered: (1) design for maximum Q when source and load resistances are specified; (2) design for maximum Q when minimum acceptable gain is specified; (3) design for maximum gain-Q product when source and load resistance are specified. Data are presented showing the trade-off between gain and Q as circuit parameters are varied.

DMA

AD 632690 QR 12

UNLIMITED

E.B. Lewis Co. Inc., East Hartford,  
Conn., U.S.A.

650.51

PRODUCTION ENGINEERING MEASURE, CRYSTAL UNIT

621.372.612

CR - (X4-46)/u (1.11.1965 - 1.2.1966)

621.315.613.7

Lewis, E.E.

U 171:1543

1966

14pp.

DL 36-039-8C-06737

The reasons for the failure of the 70 Mc/s preproduction samples are analyzed. The problem of the instrumentation limitations with particular reference to obtaining satisfactory values of C<sub>1</sub> are discussed. The redesign of the 70 Mc/s units with reference to fitness, platability and spot size are explained and documented. The revised manufacturing and testing procedures now possible with the new design are presented.

DMA

AD 637100 QR 6

UNLIMITED

Billey Electric Co., Erie, Pa., U.S.A.

047.1 BILLEY

PRODUCTION ENGINEERING MEASURE, CR-(X4-53)/U

621.372.612

QUARTZ CRYSTAL UNITS (FEB.-APRIL, 1966)

621.3.032.53

Wolfskill, J.H.

U 032:Billey Electric

19pp.

1543:103155

DL 36-039 AMC 03640(E)

Although sample crystal units have been able to meet the stated requirements, neither sealing yields nor reliability levels attain the values which we believe are possible. The difficulty has been that cracking and/or leaking of the glass holders detracts from the performance of the units. Investigations were made to find methods of reducing these losses, preferably without making changes in the designs of the crystal resonators or the holders.

DMA

AD 636007	Semit-Ann Tech. Summ. Rep. 2	UNLIMITED
	Lexington Labs., Inc. Cambridge, Mass., U.S.A.	621.3.038.8 548.5
	VAPOR PHASE GROWTH OF RUBY MONOCRYSTALS (2.1 - 1.7.1966)	549.517.13 U 14632.1044
	Scheffer, P.S. Aug., 1966	NONR-4574(00)-1
	17p., 5ref.	

The techniques of preparing large, high perfection ruby monocrystals by vapour phase growth was investigated and developed. A device was incorporated into the system which increased control of total pressure during crystal growth. Ruby crystals were successfully grown using chromium chloride and chromium carbonyl as sources of chromium vapour. Oxidation potential was determined to be an important process variable affecting  $Cr_2O_3$  concentration. Laser oscillation of a vapour-grown ruby compared to Verneuil and Czochralski-grown rubies showed it to be of high optical perfection.

DMA

P 146205	R.R. 7-001-49	ARL-66-0131	UNLIMITED
	NCA Victor Res. Labs., Montreal, Canada		
	NOISE CONSIDERATION FOR THE DETECTION OF WEAK LASER SIGNALS (1.3 - 1.6.1966)		621.303.4((535.61-15)) 621.375.826
	Waksberg, A.L., Shkarofsky, I.P. Sept., 1966		U 10542:10027:156710 AF 33(615)-2196
	56pp., 25ref.		

A study is made of the minimum laser signal that can be detected when it is embedded in a background of black body radiation and other sources of noise. In particular, the laser source is assumed to be modulated and a phase lock or pulse coincidence amplifier to be employed. General expressions are derived for the signal-to-noise ratio at the output of a phase lock (or pulse amplifier) for a signal immersed in noise. The types of modulation that are examined comprise sinusoidal, square wave and pulse modulation. The noise considered is that arising from black body and Bremsstrahlung radiation, thermal noise, generation-recombination noise etc. In particular, laser noise is discussed in some detail. Finally, a Thomson scattering experiment is considered as a special case.

DMA

AD 637500	Rep. 1405	AFOSR 66-0490	UNLIMITED
	Stanford Univ., Microwave Lab., Calif., U.S.A.		
	THE MEASUREMENT OF SEVERAL OPTICAL NONLINEARITIES USING FOCUSED GAUSSIAN LASER BEAMS		621.375.826 535.326
	Ejorkholm, J.E. Jan., 1966		535.561.1 U 14634:1051
	122pp., 30ref.		AF 49(630)-1525

The twofold purpose of this study was (1) to analyze optical second-harmonic generation (SHG) in the focus of the lowest order transverse mode of a cw gas laser beam; (2) to utilize the power enhancement available from focusing to measure smaller nonlinearities on a cw basis than previously had been done. The analysis is carried out for negatively birefringent index-matching crystals and the solution gives the dependence of the second-harmonic power upon the crystal length, the crystal double-refraction angle, and the laser beam focal spot size. The general case of a crystal anywhere along the focused beam is also presented. Interpretation of the results shows that the limiting of SHG by double refraction is determined by beam divergence, not beam radius. The second section of this study describes measurements of several optical nonlinearities in calcite which were made under conditions of optimum focusing using cw gas lasers.

DMA

AD 640439	TR ECOM 2751	UNLIMITED
	Army Electronics Command, Fort Monmouth, N.J., U.S.A.	
	INTERFEROMETRIC PHOTOGRAPHIC TECHNIQUES FOR RECORDING OPTICAL PATH LENGTH VARIATIONS IN PUMPED LASER RODS	621.375.826 535.417.2 621.3.038.84
	Bickart, C.J. Aug., 1966	U 14036:14037.15646
	20pp., 3ref.	

Describes some unique photographic techniques developed during an investigation of thermal effects occurring in solid-state laser materials (Nd glass and ruby) during the pumping period. An experimental approach is described for the investigation of the interaction of a high-energy laser beam with the atmosphere. Two novel high-speed cameras designed specifically for these investigations are discussed in detail. Experimental results are shown from which conclusions concerning optimum pumping arrangements, rod characteristics, and doping concentrations can be drawn.

F 146411 Engng Rep. 8387 N.S. CR 77482 UNLIMITED  
 NGC-35245  
 Perkin-Elmer, Electro-Optical Div., 621.375.026  
 Norwalk, Conn., U.S.A. 654.1:  
 LASER/OPTICS TECHNIQUES 629.703  
 Lipssett, H.S. U 14836  
 29.4.1966 223pp.

The subject of the present programme is laser and optical techniques applicable to future deep space optical communication systems. Analysis and laboratory work have been conducted in the following areas: stability of laser beam intensity distribution in the far field; remote boresight alignment of receiving and transmitting optical channels; isolation of the transmitter channel from the receiver channel; determination of a rotational coordinate reference system about the line of sight; and ways of implementing fine guidance tracking and pointing offset capabilities. Laboratory breadboard equipment which was developed as building blocks for this programme is described, and a summary of project activities to date is presented.

DMA

AD 637231 TDR 2939-5 FR UNLIMITED  
 RADC TR 65-450  
 Hughes Aircraft Co., Fullerton, 621.376.3  
 Calif., U.S.A. 621.385.62  
 PULSE LOCKED MICROWAVE OSCILLATOR U 1431:106342  
 (FREQUENCY MODULATOR AND EXCITER) ITEM 6 Proj. 4519  
 (PARTIAL) AF 30(602)2939  
 Bennison, G.K.  
 July, 1966 25pp.

Results of a technical study to design and supply an X-band exciter and modulator for the Passive Satellite Research Terminal (PSRT). This design supplies the necessary hardware to provide an exciter-modulator operating at 7.33 gc for X-band experiments with the PSRT.

DMA

#### CIRCUITS - PULSE, DIGITAL, PRINTED & POTTED

AD 626271 SJ 220-0056-1 CR 1 ECOM 01256-1 UNLIMITED  
 Sperry Microwave Electronics Co., 621.374.4  
 Clearwater, Fla., U.S.A. 621.302.23  
 BROADBAND HARMONIC GENERATORS U 145:150723  
 (21.6 - 21.9.1965) Proj. 1 P 6-22001 A 056  
 Chambers, R.P. D. 28-043-ANC-01256(E)  
 Oct., 1965 29pp.

The design goals for a broadband, solid state, Ku band tripler and the general circuit requirements to obtain these goals are presented. Reasons for selecting the form of the first basic tripler are discussed as well as its utilization in an alternate approach which dispenses with the idler circuit as a distinct quantity. An output filter-transformer is described and equations are derived for the relationships between hardware parameters and prototype parameters. Design curves for a three-section Tchebycheff prototype filter are included. The theoretical curves of varactor parameters are applied to a particular varactor to obtain theoretical diode parameters.

DMA

F 146223 Sci. Rep. 2 N.S. CR 77002 UNLIMITED  
 UO-011500-0 N66-36057  
 Texas Instruments Inc., Dallas, U.S.A. 621.30.049.7(S.I.C.)  
 STUDY OF SOLID-STATE INTEGRATED MICROWAVE 621.396.61  
 CIRCUITS 621.396.665.52  
 Mason, A.E., Farber, L.L. U 156772:2223:1236  
 31.3.1966 61pp., Gref. N/S 12-75

A study of a basic frequency-modulation telemetry transmitter configurations suitable for use in the 1- to 2-GHz frequency range is presented. The purpose of this study is to establish the framework within which a detailed analysis of the system requirements in terms of components, techniques, and devices can be made with the objective of demonstrating the system performance when implemented in integrated circuitry. The study includes the objective specifications, bandwidth determination, AFC control system parameters, and a discussion of eleven basic configurations.

DMA



# ELECTRON TUBES

37

AD 636650 FTD TT 65-1617/1-24 UNLIMITED  
Foreign Tech. Div., Wright-Patterson AFB., Ohio,  
U.S.A. 621,383,292  
CHANNEL PICTURE AMPLIFIERS U 156846  
(Transl. From: Slaboproudy Obzor, 24(6), 356-  
363, 1963, U.S.S.R.)  
Jares, V.

25pp., 3ref.

Methods are described which enable images to be intensified making use of secondary emission multipliers.

DMA

AD 638447 ECOM-TR 2737 UNLIMITED  
Army Electronics Command, Fort Monmouth,  
N.J., U.S.A. 621,385,632  
ULTRA-LOW-NOISE TRAVELING-WAVE TUBE 537,312,62  
Zotter, B. 621,59  
Aug., 1966 11pp., 2ref. U 156362, 1084, 1086

The influence of high magnetic fields in the gun region on the noise figure of travelling wave tubes was investigated experimentally and analytically. The experiments were performed with a superconducting magnet capable of fields up to 30,000 gauss. Noise reduction of over 2 dB was measured. The analytical work resulted in a model which attributes the dependence of noise figure on magnetic fields to the coupling of axially symmetric space charge and transverse modes. Enhancement of the coupling mechanism is predicted for annular beams and for beams in magnetic field gradients.

DMA

P 146207 FR ARL 65-186 UNLIMITED  
ITT Industrial Labs., Fort Wayne, Indiana, U.S.A. 621,385,832  
REPORT ON DEMOUNTABLE VACUUM SCANNER AND VACUUM 621,383,4  
SEALED CRYSTAL SPECIMENS FOR ELECTRONIC SCANNING 546,481,22  
Williams, R.O. U 156843 15683  
Sept., 1966 16pp. AP(33-601)-  
63-7819  
Six specially processed crystals which had been prepared were mounted into sealed-off test envelopes and partially evaluated. A demountable vacuum test head was furnished which has been utilized for testing a considerable number of specially prepared crystals.

DMA

# RADIO

NASA CR-682 UNLIMITED  
Adcon, Inc., Cambridge, Mass., U.S.A.  
ADVANCED THRESHOLD REDUCTION TECHNIQUES STUDY 621,376,9  
Filippi, C.A. U 1479  
Jan., 1967 132pp., 16ref.

The threshold improvement capabilities of feedback and band-dividing demodulation techniques are investigated for FM or PM signals having a large index and/or deviation. The threshold performance of phase-locked and frequency-compressive feedback demodulators is analyzed and an optimum second-order phase locked demodulator having a sinusoidal phase detector is developed and tested along with a conventional FM demodulator. Their threshold improvement capabilities are established and a third-order loop is developed and tested. The cycle slippage with a sawtooth phase detector is also investigated. Finally, several band-dividing systems based on either direct demodulation or signal estimation techniques are analyzed and compared to the phase-locked demodulator insofar as possible.

PDF

AD 600900 P-1353 UNLIMITED  
 Rand Corp., Santa Monica, Calif., U.S.A.  
 GENERAL DESCRIPTION OF A COOPERATIVE ANTI-  
 COLLISION SYSTEM FOR AIRCRAFT 621.396.933.2  
 Early, L.D. 621.396.969.36  
 3.2.1950 4pp. U 31.474

Some thoughts are noted on a workable, immediately available system for collision avoidance that is usable as an interim device until research can provide a better system.

DMA

#### R.D.R

RLE TR 66348 MATH 161 UNLIMITED  
 Royal Aircraft Est., Ministry of Aviation, U.K.  
 AN INTEGRAL EQUATION EIGENFUNCTION PROBLEM 621.396.96:535.312  
 CONCERNING THE ABILITY OF A RADAR TO 621.371.332.3  
 DISTINGUISH BETWEEN TWO TARGETS 621.396.969.11  
 Muddle, R.P. D 12241:414  
 Nov., 1966 13pp., 1ref.

Once the required performance of a radar has been specified by its ambiguity function, there exists an optimum emitted signal which most closely satisfies this requirement. The signal is the eigenfunction corresponding to the dominant eigenvalue of an integral equation. A numerical method is used to determine this eigenfunction and to evaluate the actual ambiguity function of the system using this signal.

DMA

AD 635052 FTD MT 65-62 UNLIMITED  
 Foreign Tech. Div., Wright-Patterson AFB,  
 Ohio, U.S.A. 621.396.969.3  
 CERTAIN QUESTIONS OF THE THEORY OF DETECTION OF 621.391  
 SINGLE PULSES (Transl. from: Trudy Leningradskogo k 413:212  
 Korablistroitel'nogo Instituta Sudostroyeniye  
 i Sudovoye Mashinostroyeniye 1962 (36), 121-  
 133, U.S.S.R.)  
 Nesteruk, V.F., Porfir'yeva, N.N.  
 14.1.1966 14pp., 0ref.

The present article is devoted, mainly, to a detailed study of special cases of detection of single pulses encountered in practice. The greatest attention is paid to the asynchronous method of detection.

DMA

#### SPACE COMMUNICATION

NASA ST-69 Vol.5 — UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 SPACE TECHNOLOGY, VOLUME V: 629.7.050.76  
 TELECOMMUNICATIONS 621.376.2:621.376.5  
 Stiffler, J.J. 629.7.035  
 1966 139pp., 13ref. U 143:13211

Discusses (1) Fundamentals, (2) Amplifiers and antennas, (3) Modulation, (4) Data Compression, (5) Tracking, in so far as these subjects are related to space technology.

DMA

N.S.A. SP 32 VOL.4

National Aero. &amp; Space Admin., U.S.A.

TELSTAR I WITH A SUPPLEMENT ON TELSTAR II

Dec., 1965

422pp., 35ref.

UNLIMITED

629.70 TELSTAR

629.703

629.7.006

Includes: Project Telstar - Fucino Earth station operation analysis; Description of the installations at the Pleumeur-Dodou space communications station (Dautry, M.J.); Results of tests performed with the Telstar I satellite at the Pleumeur-Dodou satellite communication station (Bourgeat, L., Dyevre, A., Houssin, J.P.); The Post Office satellite communication system ground station at Goonhilly, Cornwall (Bray, W.J., Taylor, F.J.D.); The Goonhilly 85-ft steerable dish aerial (Kington, C.M.); Computing and data transmission for the prediction steering of the Goonhilly satellite-communication aerial (Seaman, E.C., Thompson, W.E.); Digital techniques used in the steering apparatus of the GPO steerable aerial at Goonhilly Downs (Marshall, J.E., Coulter, R.J., Binks, J.K.); Beam-swinging facilities for the Goonhilly satellite-communication aerial (Davidson, C.F., Rawlinson, W.A.); A 4/6 Gc/s circularly-polarized diplexer for the Goonhilly

(continued)

N.S.A. SP 32 VOL.4 (continued)

satellite-communication aerial (Chakraborty, D., Millward, G.F.D.); Primary feeds for the Goonhilly satellite-communication aerial (Ravenscroft, L.A.); Waveguide Feeder system for the Goonhilly satellite-communication earth station (McDiarmid, I.P., Gordon, S.C.); The travelling wave maser amplifier in the Goonhilly radio station (Walling, J.C., Smith, P.W.); The helium system of the maser installation at the Goonhilly satellite-communication earth station (Daglish, H.N., Child, M.N.); A low-temperature thermal noise source for use at the Goonhilly satellite-communication earth station (Daglish, H.N.); Demodulation techniques for use at Goonhilly satellite-communication earth station (White, R.W., Westcott, R.J.); A high power travelling wave tube for satellite communications (Bryant, M.O., Thomas, A., Wells, P.H.); The output stage for the ground transmitter at Goonhilly (Petherham, A.R.); Results of tests at Goonhilly using the experimental communication satellites Telstar I and Telstar II (Bray, W.J., Taylor, F.J.D., White, R.W.); Communications and radiation experiments with Telstar II.

MECHANICAL ENGINEERING - GENERAL

DMA

AD 639953 MEL Rep. 412/66

Navy Marine Engineering Lab.,

Annapolis, Md., U.S.A.

UNLIMITED

621.882

MECHANICAL SHOCK RESISTANCE OF THREADED

PISTONS

Braden, J.R., Heise, R.E.

Oct., 1966

20pp., 25ref.

An investigation was made of the mechanical shock resistance of K-monel full-body studs set in HY-80 steel under various conditions. Strain gauges mounted on the stud shanks were used to measure dynamic loading. Elastic nylon-insert monel stop nuts were used throughout the test. The data indicated that for the conditions of the test Locktite-coated 3A-3B threads are equal in shock resistance to uncoated 5A-5B threads, and that the elastic stop nuts are reusable after repeated shock.

STD

ENGINES - PISTON, TURBINE, RAMJET

AD 637992

UNLIMITED

Boeing Airplane Co., Vertol Div.,

Norton, Pa., U.S.A.

621.430

DESIGN HANDBOOK FOR SUBMERGED ENGINE

621-71

COOLING SYSTEMS AND DUCT SYSTEMS

629.735-45

Jan., 1953

600pp.

NOLB 56-800-F

This handbook has been prepared to provide aerodynamic and thermodynamic data required in the design of helicopter or airship cooling and induction airflow systems. In addition, considerable data have been provided to assist in the physical design of the various internal flow components. A rather extensive bibliography has been presented; the most apparently useful works are catalogued with each appropriate chapter, while an additional extensive bibliography is presented as an entity.

STD

NASA TN D-3035

UNLIMITED

National Aero. & Space Admin., U.S.A.  
EXPERIMENTAL PERFORMANCE EVALUATION OF A  
4.59-INCH RADIAL-INFLOW TURBINE OVER A  
RANGE OF REYNOLDS NUMBER

621.436.1  
629.7.044.53

Nusbaum, W.J., Wasserhauer, C.A.  
Feb., 1967 15pp., 9ref.

An experimental investigation of a 4.59-inch-tip-diameter radial-inflow turbine was conducted to determine the effect of a change in Re on the performance of this size and type of turbine. The investigation was conducted with cold argon over a range of inlet pressures from 4.4 to 24.0 lb/in.<sup>2</sup> absolute, corresponding to a range of Re from 64 000 to 352 000, at equivalent design speed and pressure ratio. Re as used herein is defined as weight flow divided by the product of viscosity and rotor tip radius. At each value of turbine inlet pressure, data were taken at equivalent design speed over a range of pressure ratios.

VJD

LUBRICATION & BEARINGS

P 146196 NTI-65 TR 49

N66-23515

UNLIMITED

NASA CR 74401

Mechanical Tech. Inc., Latham, N.Y., U.S.A.  
DISTORTION OF GAS THRUST BEARING DUE TO  
VISCIOUS SHEAR

621.022-05  
NO. 3730(00)

Pan, C.H.T., Sternlicht, B., et al.  
Dec., 1965 26pp., 7ref.

This paper presents an analysis of thermal distortion of a gas lubricated spiral-grooved thrust bearing resulting from viscous shear. It is concluded that: (1) friction heat generated in the fluid film can distort the thrust surface and cause considerable reduction in load carrying capacity, (2) in order to minimize the frictional power losses the bearing distortion must be minimized, (3) the degree of distortion does not directly depend on the temperature level, (4) the amount of distortion is increased by a large coefficient of thermal expansion and reduced by a large coefficient of thermal conductivity, (5) large radius ratio bearings and high speed rotors are more sensitive to this type of thermal distortion, (6) analysis of a typical bearing design shows that the effects of thermal distortion can be significant for most structural materials and (7) materials giving minimum thermal distortion are often unsatisfactory otherwise. In such cases a surface coating may be applied to reduce friction and improve resistance to wear.

LBT

NASA SP 113

UNLIMITED

National Aero. & Space Admin., U.S.A.  
DYNAMIC STABILITY OF ROTOR-BEARING  
SYSTEMS

629.7.035.6  
621.022

Gunter, E.J.  
1966 220pp., 11ref.

The objective of this investigation has been to examine in general the conditions which can lead to nonsynchronous precession in a rotor system. Nonsynchronous precession, which has often been referred to as shaft whirling, oil film whirl, resonance whip, half-frequency whirl, is a self-excited motion which can be caused by several factors such as internal rotor friction and fluid film bearings. In the analysis, general equations of motion of the extended Jeffcott rotor are developed to include rotor and foundation flexibility, internal and external damping, rotor and bearing mass, and fluid film bearings.

STB

NASA TN D-3821

UNLIMITED

National Aero. & Space Admin., U.S.A.  
EVALUATION OF HIGH-TEMPERATURE BEARING CAGE  
MATERIALS

621.022.7

Zaretzky, E.V., Anderson, W.J.  
Jan., 1967 15pp., 3ref.

A cage compatibility tester was used to determine the relative wear characteristics of six cage materials with four lubricants of practical interest. Test conditions were ambient temperatures of 500 and 700 deg.F (260 and 371 deg.C) a shaft speed of 1200 rpm, and test durations of from 30 to 120 minutes. Measurements of the wear scar in the cage pocket were used to determine the effect of cage material, temperature, lubricant, and material hardness on cage wear. For the temperature range of 500 to 700 deg.F, S-Monel and M-1 materials gave the least wear. Additionally, at 500 deg.F, 400C (modified) stainless steel and a polyimide polymer indicated low wear.

QH

NASA TN D-3032

National Aero. & Space Admin., U.S.A.

ROLLING-ELEMENT FATIGUE LIFE OF SAE

52100 STEEL HOLLOW BALLS

Schibbe, H.W., Parker, R.J., et al.

Feb., 1967 15pp., 11ref.

UNLIMITED

621.022.7:

669.14.018.24:

539.431

The NASA five-ball fatigue tester was used to determine the rolling-element fatigue lives of hollow and solid 1/2-inch-diameter (12.7 mm) balls. The upper test balls fabricated from consumable vacuum melt SAE 52100 steel (Cr 1.0%, C 1.0% approx.) were run against SAE 52100 steel lower support balls. Tests were conducted at a maximum Hertz stress of 800,000 lb/in<sup>2</sup> ( $5.52 \times 10^9$  N/m<sup>2</sup>) with no heat added and with a super-refined naphthenic mineral oil as the lubricant. The hollow balls were fabricated by a technique that included rough-forming hemispherical shells, joining them together by electron-beam welding, heat treating, and finishing to an Anti-Friction Bearing Manufacturers Association 10 specification.

CRH

P 146173

ALL 65 to 32

Semi Ann Rep 3

UNLIMITED

NASA CR 54313

N66-32922

629.7.063.7

621.392

629.735((629.7.076.54))

NAS 3-6267

SKF Industries Inc., Res. Lab.,

King of Prussia, Pa., U.S.A.

SUPERSONIC TRANSPORT LUBRICATION

SYSTEM INVESTIGATION

Rhodes, W.L., Sibley, L.D.

20.5.1966 120pp., 3ref.

The performance of aircraft gas turbine mainshaft tail bearings, seals, and lubricants under simulated supersonic transport engine conditions (Mach 3) is being studied using the most advanced materials, designs, and manufacturing techniques available. Both an oil circulating system and a once-through oil-mist system are under investigation, each with inert gas blanketing for high-temperature operation. Five candidate lubricants for each of the two systems are being used in screening evaluations, and a 1000-hour endurance test will be conducted with the two test oils in each system.

STD

P 146333

TRL REP. 6456

UNLIMITED

Naval Res. Lab., Washington, D.C., U.S.A.

DRY-FILM LUBRICANTS FROM MOLYBDENUM DISULFIDE

621.392.7

DONDED WITH MICROFIBROUS BOEHMITE

546.774.222.2

Fitzsimmons, V.G., Zisman, W.A.

22.12.1966 16pp., 14ref.

Binders that have been tried for powdered lamellar dry lubricants have shortcomings such as hindering the realignment of the lubricant particles or encapsulating the lubricant, making a wearing-in process necessary. A microfibrinous form the colloidal alumina (boehmite) is shown to act as a superior nonencapsulating binder for molybdenum disulfide in the formation of dry lubricant films. Such films exhibit lower coefficients of friction than have been reported for molybdenum disulfide or graphite films bonded with any other material. These new lubricating coatings have good load-carrying ability and durability at any temperature below the decomposition temperature of molybdenum disulfide (700 deg.F.). Optimum performance of these boehmite-bonded films is obtained when (a) the ratio of fibrillar boehmite to MoS<sub>2</sub> is near 0.20, (b) the film is 0.2 to 0.5 mil thick, (c) the substrate is hard and highly polished, and (d) the film is applied as an alkaline dispersion (pH = 10) and then dehydrated by baking at 550 deg.F.

FJM

#### WORKSHOP PRACTICE

NASA TN D-3434

UNLIMITED

National Aero. & Space Admin.,

Washington, D.C., U.S.A.

621.762.34:

COMPARISON OF SELECTED SUBMICRON POWDER

621.929.1

BLENDED METHODS FOR DISPERSION ALLOYS

Norris, L.F., Reinhardt, G., et al.

Feb., 1967 27pp., 10ref.

In this investigation, a newly developed cartridge, actuated press was used to compact blended powder specimens to densities adequate for examination with the electron microscope while avoiding agglomeration due to prolonged heating at high temperatures. An automatic film scanner developed specifically for lineal analysis of dispersion microstructures was used to obtain microstructural parameters that were based on much more extensive and intensive examination than had previously been feasible. Blends consisting of 0.05-micron nickel powder with 5.4-volume-% 0.025-micron aluminum oxide were prepared by various wet and dry methods.

CRH

MILITARY SCIENCE

AD 640057 R-102-4 FR UNLIMITED  
 Computer Res. Corp., Newton, Mass., U.S.A.  
 A STUDY OF CONVERSATIONAL ON-LINE INTERACTION 519.283((355.4))  
 IN MAN-MACHINE WAR GAMING 681.3.06 JOEL  
 Clapp, L.C., Jacobson, R.V. et al. NONR 4861(00)  
 Aug., 1966 64pp., 13ref.

Describes a study of war gaming using on-line interaction between man and computer. It is concluded that analysis and war gaming capabilities can be increased significantly using a time-sharing computer system with appropriate software and remote-access terminals. A system concept called CONSORT (CONversational System with On-line Remote Terminals) is described, and specifications are given for a user-oriented, conversational language, JOEL, which is designed specifically for simulation and analysis applications. CONSORT includes an automated data library, computer programming management features, and the capability to operate computer programs written in languages other than JOEL. Computer-aided manual gaming using CONSORT is described.

LBT

P 146321 Study UNLIMITED  
 ABT Associates Inc., Cambridge, Mass., U.S.A. 355.425  
 THE URB-COIN GAME 519.283((355.4))  
 Oct., 1966 135pp. 21 49-083-082-3062

This report presents the results of a six-month effort by ABT Associates, Inc., to develop a game to simulate some of the major aspects of the terror phase of developing a computer model of urban insurgency based on game findings. Research on twenty selected cases of urban insurgency preceded development of the game, which has been played eight times to date; five times in developmental test versions, and three times in its current operational form. It has not yet been played a sufficient number of times to provide a data base for quantitative research findings.

LBT

MILITARY ENGINEERING - GENERAL

P 146787 TR 64-58 N66 37523 UNLIMITED  
 General Motors Corp., G.M. Defense Res. Labs.,  
 Santa Barbara, Calif., U.S.A. 531.58  
 MEASUREMENTS OF SHOCK WAVE PRESSURES GENERATED 623.562.3  
 BY HYPERVELOCITY IMPACTS IN ALUMINUM 669.715  
 Charest, J.A. NAS 1-1118  
 Nov., 1964 22pp., 11ref.

This paper presents and discusses the results of an experimental technique which has been used for determining maximum shock wave pressures generated by hypervelocity impacts of 0.476-cm aluminium spheres on 1100-0 aluminium targets. Shock wave pressures were calculated from available shock-wave data for aluminium using the approximation that free-surface particle velocity is twice the particle velocity behind the shock inside the targets. Measurements were made for various thicknesses of target and compared with values predicted from hydrodynamic calculations. The experimental results, which were obtained at an impact velocity of 7.32 km/sec, show a very close agreement above 100 kilobars with values calculated at 7.32 and 7.62 km/sec. From the calculated and measured values of peak shock wave amplitude, the pressure is found to decay as the inverse of the 1/4-power dependence of the distance from the impact point.

LBT

P 14654 TR 15 UNLIMITED  
 Army Cold Regions Res. & Engineering Lab.,  
 Hanover, N.H., U.S.A. 624.139  
 A STRAIGHT-WALL CUT-AND-COVER SNOW TRENCH  
 Toblason, W., Rissling, D.L.  
 Oct., 1966 39pp., 17ref.

During the summer of 1962, a straight-wall cut-and-cover snow trench was constructed at Camp Century, Greenland, to house tests performed by USA CRREL Project 33, Feasibility Study of Pile Foundations in Snow. In this report, the parameters used to design the trench and the equipment and methods used in the construction are presented and evaluated. Time-motion studies covering all phases of construction are included as a guide for the planning and evaluation of similar construction.

LBT

AD 622333 GRM-65-1 Addendum to UNLIMITED  
Final Rep.  
P 125060 623.454.9 EFFECTS  
355.58  
IIT Res. Inst. Tech. Center,  
Chicago, Ill., U.S.A.  
TRAJECTORY ANALYSIS FOR STRUCTURAL  
FRAGMENTS  
Ahlers, E.D.  
1.8.1965 94pp.  
An addendum to the Final Report on the Debris Clearance Study (P125 060).  
It contains computations of the trajectories of typical fragments subject  
to nuclear blast winds and also amended versions of certain sections of the  
Final Report.

LET

ROCKETS (INCLUDES ROCKET ENGINES)

P 146540 VIDYA NO.201(F) N66-20545 UNLIMITED  
NASA CR 54757  
Itok Corp., Vidya Res. & Dev., 621.455((662.3-404))  
Palo Alto, Calif., U.S.A. 536.422.1  
ANALYTICAL AND EXPERIMENTAL STUDY OF NLS 7-210  
ABLATION MATERIAL FOR ROCKET-ENGINE  
APPLICATION  
Rindal, R.A., Flood, D.T., et al.  
15.5.1966 242pp., 44ref.  
A combined theoretical-experimental programme was conducted for develop-  
ing techniques for rating the performance of ablative materials in liquid-  
propellant rocket engines. The theoretical studies resulted in the develop-  
ment of a computer program for characterising the response of charring  
ablation materials in high temperature, chemically reactive environments of  
arbitrary chemical composition. The experimental investigations resulted  
in the successful modification of an arc-plasma generator so that it would  
operate with the necessary gases and at the conditions requisite to achiev-  
ing simulation of ablative material response in two liquid-propellant  
environments, namely,  $O_2-H_2$  and  $H_2O_4-N_2H_4/UDPH$ .

RHC

NASA TN D-3010 UNLIMITED  
National Aero. & Space Admin., U.S.A.  
OXIDE-CATHODE DURABILITY IN MERCURY ELECTRON- 621.455. 10W  
BOMBARDMENT ION THRUSTOR 621.3.035.222.4  
Kerslake, W.H.  
Feb., 1967 25pp., 9ref.  
The results of lifetime testing of oxide cathodes in mercury discharge  
chambers at emissions of 0.3 to 0.5 ampere per square centimeter are  
presented. High cathode erosion rates, probably due to ion sputtering,  
necessitated the construction of heavy layers of wire-reinforced oxide to  
provide lifetimes up to 5000 hours. An oxide-coated brush cathode gave  
the best lifetime of any cathode operated in an actual thruster. Operation  
at low discharge voltages greatly extended the lifetime of cathodes.  
Calculated and measured losses of the oxide coating are compared.

VJD

NASA TN D-3022 UNLIMITED  
National Aero. & Space Admin., U.S.A.  
EXPERIMENTAL INVESTIGATION OF ACOUSTIC 621.455.019.2  
LINERS ) SUPPRESS SCREECH IN HYDROGEN-  
OXYGEN ROCKETS  
Wanhainen, J.P., Bloomer, H.E., et al.  
Feb., 1967 41pp., 16ref.

An investigation of suppression of high-frequency combustion instability  
using Helmholtz type acoustic damping devices was conducted at the Lewis  
Research Centre in a hydrogen-oxygen rocket of nominally 20,000-pound thrust  
size. Acoustic liner design variables investigated include the number and  
the diameter of the apertures, the thickness of the liner, the length of  
the liner, and the gap height behind the liner. The tests were conducted at  
a chamber pressure (nominal) of 300 pounds per square inch absolute and a  
range of oxidant-fuel ratios from 4 to 6. Hydrogen injection temperature was  
used to rate the stability of the various liners. The liner with the lowest  
self-triggering temperature was considered to be the most stable design.

VJD

NASA TN D-3359

UNLIMITED

National Aero. &amp; Space Admin., U.S.A.

AEROBEE 150 PROFUSION FAILURE

629.76 AEROBEE

Busse, J.R., Bushnell, P.S.

551.507.362.1

Feb., 1967

37pp., 10ref.

NASA vehicle 4.113 G1-G1, an Aerobee 150 launched from the White Sands Missile Range, New Mexico, in April 1964, experienced a "hard" start (an explosive initial combustion generating high chamber pressures) which resulted in other anomalies, including a tail cone explosion after 27 seconds of flight. The most probable cause of the hard start was an improper rupture sequence of the fuel and oxidizer diaphragms which could have resulted from an improper fuel bleed or manufacturing discrepancies. As a result of corrective measures, no hard starts occurred in 10 later Aerobee flights in 1964.

MHC

EXPLOSIVES & PROPELLANTS

AD 632461

NRDL-TR-1002

UNLIMITED

Naval Radiological Defense Lab.,

San Francisco, Calif., U.S.A.

546.171.5

THE RADIOLYTIC DECOMPOSITION OF

539.1.04

HYDRAZINE, RP-1 AND HYDRAE ROCKET

662.3-404 FUELS

FUELS

Shelborg, W.E.

6.3.1966

11pp., 8ref.

100-ml. samples of the storable liquid rocket fuels hydrazine, RP-1 and Hydrazine generate, respectively, 39.1, 50.3 and 149.4 ml. of radiolytic off-gas (measured at 25 deg.C and 1 atm) when irradiated to  $0.5 \times 10^6$  rads with gamma rays. When approximately 5 wt.% of an efficient olefinic free-radical scavenger is added to the samples, the off-gas volume produced by RP-1 fuel is reduced by 18.7% while those of hydrazine and Hydrazine fuels are not reduced. These scavenging effects show that RP-1 fuel decomposes radiolytically by both free-radical (18.7%) and molecular mechanisms, and that hydrazine and Hydrazine fuels decompose entirely by a molecular or ionic mechanism.

MHC

STRUCTURAL ENGINEERING

AD 646300

AFFDL TR 66-60

UNLIMITED

Air Force Systems Command, Flight

Dynamics Lab., Wright-Patterson AFB., U.S.A.

051.3 OCT. 1965

MATRIX METHODS IN STRUCTURAL MECHANICS.

624.07

(PROCEEDINGS OF THE CONFERENCE HELD AT

629.7.02

WRIGHT-PATTERSON AIR FORCE BASE, OHIO,

26-28 OCTOBER, 1965)

Przemieniecki, J.S., Dador, R.M., et al.

Nov., 1966

973pp.

The purpose of the conference was to discuss the recent developments in the field of matrix methods of structural analysis and design of aerospace vehicles. The thirty-six papers presented were arranged into six sessions under five different themes: General Matrix Methods, Finite Element Properties, Nonlinear Effects, Dynamics, and Applications. The papers cover practically all major aspects of recent research and development work in the field of matrix methods of structural analysis and design.

NASA CR 705

UNLIMITED

Massachusetts Inst. of Tech.,

Cambridge, U.S.A.

624.073.1

ON THE DUALITY BETWEEN THE PROBLEMS OF

539.305

STRETCHING AND OF BENDING OF PLATES

539.304

Elias, Z.M.

Jan., 1967

60pp., 5ref.

The analogy between the problems of stretching and of bending of plates has been known for more than half a century. A general analogy exists between the two problems and is a particular case of the static geometric analogy in shell theory. It takes the form of a complete duality between the basic equations of the two problems whereby one set of equations is transformed into the other set by interchanging according to a certain correspondence the dependent variables of the two problems. The purpose of this paper is to present this duality in its totality including in the stretching problem displacements, strains, and in-plane changes of curvature and in the bending problem stress functions, stress couples and transverse shears. In both problems, the displacement and the stress function methods of solution, displacement and force boundary conditions and simply and multiplicitously plates are considered.

STD



NACA TTF-234      ICT 1402      UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 DYNAMICS AND STRENGTH OF SHELLS      624.074.4  
 (Transl. From: Russian Book published      533.6.013.422  
 by Moscow Univ., 1963)  
 Ogibalov, P.M.  
 1963      319pp., 100ref.  
 Contents: Fundamental information on shells. Elastic vibrations of shells.  
 Flutter in panels and shells. Some other dynamic problems of shells.  
 Stability of shells in the range of elasticity. The stability of shells  
 beyond the elastic limit. Special problems in calculation of shells.  
 VJB

P 146147      ONEIL      UNLIMITED  
 Note Technique 102  
 Office National D'Etudes et de Recherches      524.074.4:  
 Aéronautiques, France      539.371  
 ON THE DETERMINATION OF SHELLS BEYOND THE  
 ELASTIC RANGE (IN FRENCH)  
 Valli, R.  
 1960      116pp., 29ref.  
 A general shell theory, including all shapes and loads, is developed, using  
 the principle of virtual displacements where they are compatible with the  
 Kirchhoff-Love assumptions extended to take account of the thickness vari-  
 ation. This has the advantage of giving directly the necessary and suffi-  
 cient conditions for equilibrium as well as the boundary-conditions concern-  
 ing the above assumptions. The equations are first written in their  
 intrinsic form and then developed in a local reference system. A general  
 law applicable to the behaviour of the material is proposed and introduced  
 in a step-by-step method permitting the calculation for large deformations  
 and beyond the elastic range (plasticity and creep).

#### AIRCRAFT EQUIPMENT & FLIGHT CONTROL SYSTEMS

AD 62516      Rep. 101      NADC-4E-6522      UNLIMITED  
 Larry Controls Inc., Watertown, U.S.A.  
 DESIGN GUIDE FOR POLYURETHANE FOAM      621-752  
 ISOLATION SYSTEMS      673.664-496  
 Calcesterri, P.C.      N600(19)59:90  
 2.12.1965      120pp., 7ref.  
 The advantages of buckling isolators over presently used military standard  
 isolators for the protection of equipment aboard high performance jet air-  
 craft are discussed. The dynamic performance of various foams is compared  
 to the theoretical behaviour of buckling isolators based on the experimental  
 results obtained with polyurethane foams. Design guides are presented for  
 the use of polyurethane foams in multifunctional vibration and shock isola-  
 tion systems based on the experimentally determined dynamic properties of  
 the foam material.

STB

#### AIRCRAFT INSTRUMENTS

RAE TR 66316      BLEU 74      UNLIMITED  
 Royal Aircraft Est., Ministry of  
 Aviation, U.K.      621.396.933.23  
 AUTOMATIC LANDING - RECENT R.A.E.      620.7.051.83  
 CONTRIBUTIONS      D 554  
 Armstrong, D.D.  
 Oct., 1966      12pp., 4ref.  
 Presents a brief review of the more important R.A.E. work on automatic  
 landing during the last four years. Work on roll-out and taxiing problems  
 in low visibility and on the pilot's role in an automatic landing are men-  
 tioned briefly; but the paper dwells particularly on some lessons learnt  
 while verifying that the I.L.S. could be used for landing, and on the  
 implications of the safety target that must be met before blind automatic  
 landing becomes a commercial reality.

DRL

AIRCRAFT

AD 635568 FSTC-HT-23-104-C6 UNLIMITED  
 Army Foreign Science & Tech. Center,  
 Munitions Building Washington, D.C., U.S.A. 629.73 JANTONOV 22  
 WINGED GIANT. (Transl. from: Nauk i Zhizn 629.746.5  
 1965 (10), U.S.S.R.)  
 Pipko, A.  
 1965 11pp.  
 A general description is presented together with some of the rationale behind its arrangement of the Antonov 22 turboprop military transport. Particular emphasis is placed on the twin-tail, high wing location, fuselage mounting of gear, variable tyre pressure and ramp geometry. The aircraft was first shown to the western world at the Paris Air Show in 1966.

STD

AIR TRANSPORT (INCLUDES AIR TRAFFIC CONTROL)

NASA TT F-0369 N66-29403 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 PROBLEMS OF APPROACH DURING POOR VISIBILITY 621.396.933.23  
 Grenillet, M.J. 629.74051.83  
 Feb., 1963 9pp. U 554  
 Although many blind landings have been made so far in various countries, there has never been any system safe enough to permit all-weather landings of airline planes. A first step towards a solution of the problem has been taken by the use of the ILS system. The ILS system defines the localizer axis to within  $\pm 1/3$  of a degree with respect to the runway axis, which leads to too great a tolerance on the lateral error. It therefore appears logical to try to improve the ILS azimuthal precision, and tests along these lines have led to the conclusion that such improvement is possible.

DMA

SPACE SCIENCE

NASA TN D-3050 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 PREDICTIONS OF SHOCK-LAYER RADIATION FROM 533.6.011.72  
 MOLECULAR BAND SYSTEMS IN PROPOSED 523.42  
 PLANETARY ATMOSPHERES 523.43  
 Woodward, H.T.  
 Feb., 1967 47pp., 31ref.  
 Concentrations of radiating molecules and radiation from a number of band systems are presented for equilibrium shock-layer temperatures and densities of vehicles entering proposed Martian and Venusian atmospheres. The atmospheres selected consist of various proportions of CO<sub>2</sub>, N<sub>2</sub>, and H<sub>2</sub>. Charts are also presented which relate these equilibrium shock-layer properties to flight velocity and ambient density through the normal shock conservation equations. These data can be used to estimate stagnation-point radiative heat transfer for entry trajectories. Estimates for a few selected flight conditions are discussed and compared.

VJB

AD 604416 R 64 BD 50 UNLIMITED  
 General Electric Co., Missile & Space Div.,  
 Philadelphia, Pa., U.S.A. 620.152((523.152))  
 PARAMETERS, TECHNIQUES AND SIGNIFICANCE OF  
 SOLAR SIMULATION IN SPACE SIMULATION TEST  
 CHAMBERS

Lee, D.E., Steg, L.  
 Aug., 1964 45pp., 5ref.  
 A review of the significance of solar simulation (collimation, spectrum, etc.) on a typical satellite is given. Parameters affecting construction and performance of the solar simulation system and its relationship to a large (32 ft. x 54 ft.) space chamber located at the General Electric Valley Forge Space Technology Center are presented. Performance data of the complete chamber and sun system and early test results of typical satellite systems are reviewed.

VJB



NASA TMX-56149 N65-19695 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 SCIENTIFIC EXPLORATION OF SPACE AND ITS CHALLENGE TO EDUCATION 629.78  
 Oct., 1964 30pp. 910

A talk commemorating the founding of Worcester Polytechnic Inst., 100 years ago. Space research is characterized by the general spirit of inquiry into the nature of the external physical world and shows the scientist using hardware developed by the engineer. The most imposing challenge of the space age is the potential feed back of its developments into the civilian economy.

VJB

NASA SP 108 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 CONFERENCE ON SPACECRAFT STERILIZATION 614.48  
 TECHNOLOGY, BECHTEL AUDITORIUM, PASADENA, 629.78  
 CALIFORNIA, NOV. 16-18, 1965 061  
 630pp.

This conference was convened to bring together scientists, engineers and administrators concerned with spacecraft sterilization technique. The seven sessions were entitled respectively (1) Sterilization requirements (2) Microbiological contamination control, microbiological monitoring and visual monitoring (3) Microbiological decontamination and sterilization (4) Bioengineering (5) Sterilizable capsule components and subsystems (6) Capsule structures and payloads, procedures and facilities (7) General Summary and panel discussion.

FAM

NASA TT F-429 IPST 1015 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 MOTION OF AN ARTIFICIAL SATELLITE ABOUT ITS CENTER OF MASS (Transl. from: Russian Book 629.783  
 published in Moscow, 1965) 531.352  
 Beletskii, V.V.  
 1966 261pp., 96ref.

Contents: Analysis of torques on a satellite; Stabilization and libration of the satellite in a Newtonian force field; Additional factors influencing stabilization and libration of a satellite; The relations between translational and rotational motions of a rigid body in a Newtonian force field; Perturbed rotational motions of a satellite and equations in osculating elements; Gravitational perturbations in rotational motion; Aerodynamic perturbations in rotational motion; Analysis of secular perturbations under the combined influence of gravity and aerodynamic torques and orbit evolution; The influence of magnetic fields and of solar radiation torques on satellite spin and attitude; The motion of some orbited artificial earth satellites around the centre of mass; Uses of an earth-oriented satellite in solar research; Motion of a rigid body about a fixed point in a Newtonian force field; The orbit of an equatorial earth satellite.

VJB

P 146115 ESRO TM-21 UNLIMITED  
 European Space Res. Organisation,  
 Paris, France 629.783  
 THE ACCURACY OF MAGNETIC ASPECT MEASUREMENTS 550.38  
 ABOARD A SATELLITE: GEOMETRICAL CONSIDERATIONS  
 Kalweit, C.C.  
 Nov., 1966 30pp., 2ref.

In the determination of the magnetic aspect aboard a satellite, errors occur due to inaccuracies of the measurement and also to the noninstantaneous sampling of the instrument outputs. The angular aspect errors resulting from these system errors are studied without discussing the measurement errors themselves. General formulae and numerical examples are given for the relation between error-angles, system errors and attitudes.

VJB

NASA CR 665	UNLIMITED
Arizona State Univ., Tempe, U.S.A.	
ATTITUDE STABILITY OF A SPINNING PASSIVE	533.6,013.7
ORBITING SATELLITE	629.783
Neirovitch, L., Wallace, P.B.	629.7,062.2
Jan., 1967	216pp., 36ref.

Mathematical techniques for the stability investigation of the motion of satellites described by nonautonomous systems of equations, and in particular systems with periodic coefficients are considered. The methods of analysis have been applied to the problem of a slightly asymmetric satellite with arbitrary spin confined to a circular orbit and the problem of a spinning symmetric satellite moving in an elliptic orbit of low eccentricity.

VJB

RLE TR 66360	SPACE 178	UNLIMITED
Royal Aircraft Est., Ministry of Aviation,		
U.K.		531.352
ORBIT DETERMINATION FROM MINITRACK		629.783
OBSERVATIONS		629.7,086
Gooding, R.H.		
Nov., 1966	17pp., 10ref.	

Although Minitrack observations are only accurate to about 1 minute of arc, accurate orbits have been obtained for a number of satellites. This is due to the excellent global coverage of the U.S.A. Minitrack network. The accuracy obtained for eccentricity is typically about  $10^{-3}$ , and comparable values are obtained for the other orbital elements. The main source of observational error is thought to be inadequate correction for ionospheric refraction. Apparent error arises through deficiencies in the orbital model, namely, inadequate representation of satellite perturbations due to the Earth's tesseral harmonics and to atmospheric drag.

VJB

NASA TR D-3873	UNLIMITED
National Aero. & Space Admin., U.S.A.	
ANALYSIS OF SEXTANT NAVIGATION MEASUREMENTS	522.41
DURING LUNAR MODULE RENDEZVOUS	629.787
Murtagh, T.E.	523.3
Feb., 1967	50pp., 3ref.

Two methods are presented for optimising individual spacecraft-star navigation measurements along the nominal concentric flight plan rendezvous trajectory for the Apollo programme. In the first method, a star is selected which will minimize the relative root-mean-square position errors at the measurement time. In the second method, a star is selected which will lie closest to the measurement plane defined by the inertial position vectors of the Command Service Module and the Lunar Module.

VJB

#### SPACECRAFT

P 146112	ECN, 22-76	UNLIMITED
European Space Res. Organisation,		
Paris, France		629.7,062.2
ATTITUDE CONTROL BY PURE JET SYSTEMS		533.694.6
O'Hanrahan, K.J.		
April, 1966	27pp., 6ref.	

Investigation of satellite attitude control systems using gas jets by the phase plane, describing functions and other techniques is described. Brief mention is made of the acquisition problems and of the electronic circuits associated with the jet valves.

VJB

NASA TN D-3854

National Aero. & Space Admin., U.S.A.  
A DESIGN METHOD FOR AN OPTIMAL ATTITUDE  
REGULATOR FOR A SPINNING SPACE STATION  
Remper, P.S.

UNLIMITED

629.7.062.2

629.786.2

Feb., 1967 38pp., 7ref.

A study was made to show how a method in optimal control could be used in the design of a linear-feedback attitude regulator for a spinning space station. The design method is for linear systems, and the regulator, operating cyclically, minimizes a final error and uses a fixed amount of control effort in each cycle of operation. The resulting optimal feedback gains for the optimal regulator are computed and presented.

VJE

P 146441

Rep. 3792009

IAC Paper N32

UNLIMITED

N64-11992

Cruikank Aircraft Engineering Corp.,  
N.Y., U.S.A.

522.15

629.783

ANGULAR CONTROL OF THE OAO SPACECRAFT UTILIZING  
THE EARTH'S MAGNETIC FIELD (25.9-1.10.1963)

629.7.062.2

N65 5-814

Paiken, N., Floizig, R.  
1963 42pp., 16ref.

The analysis and preliminary design of an advanced control technique which is incorporated in the Orbiting Astronomical Observatory (OAO) are presented. In this technique the momenta of inertia wheels, which provide the basic control torques, are regulated by torques created by the interaction of current-carrying coils with the earth's magnetic field. Operation of momentum control in this way permits an extremely accurate spacecraft pointing capability for long periods of time. This technique is applicable to any inertia wheel attitude control system for spacecraft which operate in ambient magnetic fields.

VJB

NASA SF 119

UNLIMITED

National Aero. & Space Admin., U.S.A.  
ARIEL I: THE FIRST INTERNATIONAL SATELLITE  
EXPERIMENTAL RESULTS  
1966 158pp., 71ref.

629.78 ARIEL I

The emphasis is on outlining the events that occurred during the period from launch to the end of the useful life of the satellite in November, 1974, and on documenting the results of the experiments carried aboard the satellite.

VJB

NASA MISC 295

N63-13798

UNLIMITED

National Aero. &amp; Space Admin., U.S.A.

S-6, AN AERONOMY SATELLITE

629.78 S-6

Horowitz, R.

551.507.362.2

27.12.1962 22pp.

The S-6 satellite is one of the NASA Goddard Space Flight Center's scientific earth satellites, instrumented to obtain data which will improve our understanding of the physical and chemical processes occurring in the upper atmosphere between 250 to 900 kilometres. This spherically shaped spacecraft, made from 0.025 inch thick stainless steel, is 35 inches in diameter, weighs 400 pounds, and will be launched by a Delta vehicle in the first quarter of 1963 from the Atlantic Missile Range. The satellite will be placed into a 60 degree orbit, and it will be spin stabilized at 1.5 cycles per second. A three month useful life is anticipated.

VJB

NASA SP-69 Vol.4  
National Aero. & Space Admin., U.S.A.  
SPACECRAFT GUIDANCE AND CONTROL  
Scull, J.R.  
1966 143pp., 12ref.  
Contents: Spacecraft guidance philosophy; Optical sensors; Gyroscopes; Accelerometers; Servomechanisms; Analog computers; Digital computers; Spacecraft power; Spacecraft control systems; Inertial guidance; Earth-based midcourse guidance; Celestial navigation; Lunar-landing guidance; Planetary approach guidance; Capsule control.

UNLIMITED

629.78

629.7.05

629.7.026.5

VJB

NASA T X-56997 N66-12973  
National Aero. & Space Admin., U.S.A.  
SATELLITE SITUATION REPORT  
(Goddard Space Flight Center, Space  
Operations Control Center, Vol.5, No.20)  
31.10.1965 53pp., of tables  
This report reflects data computed and compiled by the Goddard Space  
Flight Center, Norad, and Smithsonian Astrophysical Observatory as of  
1200Z on October 31, 1965.

UNLIMITED

531.352

629.78

VJB

NASA MISC 296 N66-32051  
National Aero. & Space Admin., U.S.A.  
FINE POINTING CONTROL FOR THE ORBITING  
ASTRONOMICAL OBSERVATORY (OAO)  
Graham, G.E.  
4pp., 3ref.  
High pointing accuracy requirements are imposed on the control system of the OAO. One tenth arcsec angular accuracy can be achieved in orbiting spacecraft using star references, long focal length optical systems, and relatively small torquing devices. Noise problems are introduced when a single error sensor is required to track stars with greatly different magnitudes. As star magnitude decreases, the compensating increase in the gain by the automatic gain control decreases the signal-to-noise ratio and degrades the pointing accuracy.

UNLIMITED

522.15

629.783

VJB

P 146228 LR 17516 NASA CR 60623  
Lockheed California Co., Burbank,  
Calif., U.S.A.  
STUDY OF A ROTATING MANNED ORBITAL SPACE STATION  
4.2.1964 153pp.  
Contains the visual data used by the Lockheed-California Company at the Final Oral Presentation for the study of a rotating, manned, orbital space station. The design of the station has been accomplished. The configuration on which the study was based has three modules arranged radially around a central hub. Comparisons are drawn between this configuration and two others.

UNLIMITED

629.786

N.S. 9-1665

VJB

NAS. TR X-55114      NC5-12610      UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 ADVANCED ORBITING SOLAR OBSERVATORY      629.786  
 DEVELOPMENT TASKS      522.15  
 2.12.1964      10pp.

The major objectives of the effort outlined are: Concentrate on the solution of critical problems, for example Fine Sun Sensor, and in-orbit alignment stability; Hold intact key members of the development teams which have been established at both the contractor's and major sub-contractors' facilities; Further define the observatory requirements; Prepare for system breadboard integration tests; Develop an observatory design configuration which provides the best compromise between performance, reliability, cost, and development schedule; and Minimize the number of alternate approaches or design changes for consideration in the Phase II programme should it be authorized.

VJB

P 146395      UNLIMITED  
 Air Force Systems Command, Aero  
 Propulsion Lab., Wright-Patterson AFB,  
 Ohio, U.S.A.      629.796  
 EXPANDABLE AND MODULAR STRUCTURES TECHNOLOGY      629.7.021.5  
 FOR SUPPORT OF MANNED MISSIONS, PRESENTED AT      061.3 \*10.1966  
 THE 17TH INTERNATIONAL ASTRONOMICAL  
 FEDERATION CONGRESS OCTOBER 10-15, 1966,  
 MADRID, SPAIN  
 Forbes, F.W., Yarymovych, M.I.  
 1966      14pp.

Describes up-to-date expandable and modular structures technology and its application to space missions. Historical accomplishments are reviewed, major research results are given, and immediate and longer range manned applications are included.

VJB

P 146114      ESRO SP-15      UNLIMITED  
 European Space Res. Organisation,  
 Paris, France      629.786.2  
 SPACECRAFT TECHNOLOGY. VOL.VIII: THE  
 ORBITING ASTRONOMICAL OBSERVATORY  
 Oct., 1966      25pp.

Deals primarily with the areas of satellite design in which difficulties arose in the development of the Orbiting Astronomical Observatory (OAO). A brief account is given of the history of the project, followed by a description of the OAO and its command and data handling system. The scientific experiments selected for the first three OAO spacecraft are described.

VJB

#### MECHANICAL PROPERTIES OF MATERIALS

AD 639314      FR      UNLIMITED  
 Massachusetts Inst. of Tech.,  
 Metals Processing Labs., Cambridge, U.S.A.      539.374  
 DEFORMATION PROCESSING OF ANISOTROPIC METALS      NOW 66-0068-d  
 (1.7.1965 - 30.6.1966)  
 Backofen, W.A., Holt, D.L., et al.  
 July, 1966      100pp.

Contents: Superplasticity in the Al-Cu eutectic alloy; Superplasticity in some titanium and zirconium alloys; Superplasticity in some electroplated composites of lead and tin; Superplasticity in pellet - and ingot-extrusion of the magnesium alloy ZK60.

GM



P 146468

1866-33404  
NLSL CR 77030

UNLIMITED

William Marsh Rice Univ.,  
Houston, Tex., U.S.A.  
EASY GLIDE IN MOLYBDENUM CRYSTALS  
Whitliffe, L.D., Bretzen, F.R.  
1966 5pp., 5ref.

669,28-172;  
539,306  
Grant NS 0 6-59

by using direct shear on the (110)  $\{111\}$  system of 0.125 in. dia., electron-beam zone-refined molybdenum crystals, easy glide was observed at temperatures greater than 300 deg.K for a shear-strain rate of  $4 \times 10^{-5}$  sec<sup>-1</sup>. It is noted that at higher strain rates a greater temperature is necessary for the observation of easy glide. The extent of the easy glide was dependent on the purity of the crystals, and slope of the stress-strain curves in the easy-glide region depended upon temperature and strain rate. The sensitivity of easy glide to impurities might be related to increased flow stresses in the impure material which enhance secondary slip.

QTH

AD 640160 FR ARD 4266:4

UNLIMITED

Massachusetts Inst. of Tech.,  
Mechanical Engineering Lab.,  
Cambridge, U.S.A.  
SURFACE ENERGY EFFECTS IN SLIDING  
FRENKEL (1.7.1963 - 30.6.1965)  
Rabinowicz, E.

531.44  
539.621  
539.211  
D. 31-124 ARD(D) 143

12.9.1965 91pp., 33ref.

It has been proposed that surface energy manifests itself in a sliding system through a characteristic distance, equal to the size of wear particles for that system. This hypothesis was tested in systems in which other distance parameters were introduced, namely abrasive particles of varying sizes, solid films of varying thickness, and sliding surfaces of varying roughness. A minimum load was postulated below which low wear rates would prevail, and a number of experiments were carried out to test this prediction. The effect of material compatibility on friction and wear were evaluated. The experimental results either agreed with the predictions of the surface energy model, or at any rate were not inconsistent with them.

STB

TESTING OF MATERIALS

P 146471 TR 65-359-6

INCO REP.  
NLSL CR 75505  
NLSL-27962

UNLIMITED

Aveco Corp., Tulsa Div., Okla., U.S.A.  
EVALUATION OF THERMAL CONTROL CONTING IN  
THE SPACE ENVIRONMENT

620.162(523.152)  
NLSW 1162

Cooley, J.M.

1.11.1965 13pp., 2ref.

A space environment simulation facility and equipment used for the facility space programs are described, and the methods used in the calibration and monitoring of the various parameters are discussed. Space environment simulator test equipment described are:- (1) a Van de Graaff accelerator; (2) ultra high vacuum chambers; (3) the transition section and beam scanner; (4) the solar simulator; (5) the vacuum ultraviolet source; (6) the sample holder. The reflectance measuring apparatus and the temperature control unit are also described. Schematic diagrams of the simulator and the ultra high vacuum system are given, along with a photograph of the sample holder.

MHC

AD 631342 TDR ML-TDR-64-97

UNLIMITED

Kenselner Polytechnic Inst.,  
Troy, N.Y., U.S.A.  
SURFACE TEMPERATURES AT SLIDING INTERFACES  
IN VACUUM AND METAL ADHESION (15.11.1963-  
15.2.1964)

620.178.16;  
539.538;  
539.61  
AF 33(657)-10058

Ling, F.F.

March, 1964 52pp., 38ref.

A friction and wear apparatus is described for use in vacuum which has no supporting bearings other than the sliding surfaces whose friction and wear characteristics are to be investigated. The moving specimen is suspended and rotated magnetically, external to a vacuum chamber enclosing the test section. The apparatus is suitable for both steady operation and coast-down operation. The geometries of specimens are kept simple. Surface temperatures on both sides of the interface are measured indirectly. Temperatures on the stationary specimen are measured by thermocouples while the temperature on the moving specimen is measured by a thermistor and the associated signal telemetered out from the test chamber.

QTH

NASA TN D-3820

UNLIMITED

National Aero. &amp; Space Admin., U.S.A.

STRESS INTENSITY FACTORS FOR CRACKLINE-  
LOADED EDGE-CRACK SPECIMENS

620.178.2:

539.56:

Brawley, J.E., Gross, B.

539.319

Feb., 1967 19pp., 17ref.

Crackline-loaded edge-crack specimens are flat plate specimens which have a single crack notch extending normally from one edge and which are loaded in tension at positions close to the intersection of the crack with that edge. Stress intensity factors were determined for a variety of these specimens, all with straight boundaries, by boundary collocation of the Williams form of stress function. The boundary conditions were determined with the aid of another stress function due to Filon. The results presented are considered to be comprehensive enough for a wide variety of applications of these specimens.

GHI

P 146477

C 68253

NASA CR 77395

UNLIMITED

Q.

N66-34804

661.877.651:

Arthur D. Little, Cambridge, Mass., U.S.A.

620.194.8

THE PEEL PHENOMENON IN INTERMETALLICS

NASA 1403

Berkovitz, J., Rossetti, M.

29.7.1966 9pp., 2ref.

Single crystal boules of molybdenum disilicide were prepared to perform static fatigue tests in order to correlate failure measurements in the so-called pest range with classical chemical kinetic measurements. The pest phenomenon refers to the powdery yellow oxide, a mixture of  $\text{SiO}_2$  and  $\text{MoO}_3$  which is observed on fracture surfaces. Since static fatigue curves must be obtained as a function of temperature, particular attention was given to controlling the base level strength of the crystals; and measurements made on four samples cut at random found this strength to be  $51,000 \pm 3500 \text{ lb/in}^2$ .

GHI

MATERIALS (NON-METALLIC)

AD 630299

AFIL-TR-66-131

UNLIMITED

Air Force Materials Lab., Wright-Patterson

AFB, Ohio, U.S.A.

661.636.2

GEOMETRICAL EFFECTS OF FILAMENT TWIST ON  
THE MODULUS AND STRENGTH OF GRAPHITE FIBER  
REINFORCED COMPOSITES (OCT., 1965-JAN., 1966)

673.046

Proj. 7340

Whitney, J.H.

May, 1966 12pp., 4ref.

Using basic theory previously appearing in the literature, equations are derived for determining the effects of yarn twist on the modulus and strength of graphite reinforced composites. In the strength analysis the variation of individual filament properties is considered. Results show that a few turns of twist per inch have little effect on either modulus or strength. However, these properties decrease in value rapidly beyond seven turns per inch. The theory was checked using data from a unidirectional composite reinforced with graphite yarns having approximately five turns of twist per inch.

GHI

P 146283

UNLIMITED

Harrison-Walker Refractories Co.,

Pittsburgh, Pa., U.S.A.

666.763/764

STABILITY OF COMMERCIAL REFRACTORIES IN  
VACUUM

621-982

Bonar, K.M., Cunningham, J.L., et al.

3.11.1966 25pp., 3ref.

A study has been made of the behaviour of a number of commercially available refractory materials in vacuum at temperatures to  $3000 \text{ deg.F}$  ( $1649 \text{ deg.C}$ ). Weight loss data on ten refractories are reported along with chemical analyses and petrographic observations. High alumina, magnesia, magnesia-chrome, dolomite, and stabilized zirconia type materials were included.

GHI

AD 628194 Transl. 2059  
Dept. of the Navy, Washington, D.C.,  
U.S.A.

UNLIMITED

667.637

RAPID METHODS OF TESTING ANTIFOULING  
PAINTS FOR OCEAN GOING SHIPS  
(Transl. from: OB USKORENENIYKH METODIKH  
ISPYTANIY. NEOBRISTAYUSHCHIKH KRABOK  
DLYA MOREKIKH SUDOV. L'vovskoye  
Materialy i ikh Primeneniye 1964, (6)  
51-56, U.S.S.R.)

Olotov, V.N., Gurevich, Ye.S., et al.

11pp.

The Kinetics of the process whereby copper ions, toxic to marine organisms are leached from anti-fouling coating of KAV-53 and KKB-79 has been studied. It is shown that the process taking place at different temperatures, chloride concentrations and pH values of leaching media follows a similar pattern for both paints, although temperature is the most important factor. It is recommended that the glycine method be used for the rapid determination of the speed of leaching out of copper from anti-fouling paints.

FAM

RAE TR 66299 CPM 87  
Royal Aircraft Est., Ministry of  
Aviation, U.K.

UNLIMITED

539.42:

677.015

SNATCH-TEARING OF FABRICS: COMPARISON  
OF SIX FABRICS

Swallow, J.E., Mikolajewski, E.  
Sept., 1966 25pp., 1fig., 2ref.

The snatch-tearing method developed by Swallow and Mikolajewski has been used to compare the response to a tearing agency of six biaxially-tensioned fabrics. The sum of the warpwise and weftwise torn lengths has been taken as the criterion of tear. Analysis of variance has been made and response equations determined, characterizing the length of tear in terms of the significant factors. The dependence of tear length on energy input is closely linked with the breaking strength of the fabric. The relationship for the six fabrics is very close to the hyperbolic form.

P 146120 Plastics Note 14  
Picatinny Arsenal, Plastics Tech.,  
Evaluation Center, Dover, N.J., U.S.A.  
GLOSSARY OF PLASTICS TERMS: A CONSENSUS  
Beach, N.E.  
Dec., 1966 88pp., 21ref.

UNLIMITED

678

083.7

Presents a glossary of terms relating to plastics, adhesives and elastomers; materials and techniques. It represents a consensus of opinion from various general and specific glossaries available. Terms defined are thus general or esoteric. Definitions which tie-in with plastics and the related materials are included only; available dictionary definitions are not used. 21 lists were consulted and the terms defined number over 1,800.

MHC

P 146121 Plastics Note 15  
Picatinny Arsenal, Plastics Tech.,  
Evaluation Center, Dover, N.J., U.S.A.  
FERROCENE POLYMERS: AN ANNOTATED  
BIBLIOGRAPHY  
Levi, D.W.  
Sept., 1966 24pp., 46ref.

UNLIMITED

016:

678

547.514.721:172

An annotated bibliography of 46 items is reported on ferrocene polymers. It is limited to the references in the author's personal file. However, these cover the significant journals in the field, for the period 1956-1966. Complete subject and author indexes are included for the convenience of the user.

MHC

P 146118 Plasteo Rep.56 UNLIMITED  
 Picatinny Arsenal, Plastics Tech.,  
 Evaluation Center, Dover, N.J., U.S.A. 678  
 DIRECTORY IN PLASTICS-KNOWLEDGEABLE 058.7  
 GOVERNMENT PERSONNEL (REVISED) 5.007  
 Beach, N.E.  
 Sept., 1966 144pp.

The revision has been expanded beyond the Departments of the Army, Navy and Air Force, to include the Departments of the Treasury; Commerce; Agriculture; the Interior; Health, Education and Welfare; and Housing and Urban Development. Included also are Government-funded information agencies, and the National Aeronautics and Space Administration. Contributions from 88 activities are presented, covering over 500 persons who are variously specialized in subjects pertaining to the plastics field. An index of personnel is included for use in the location of a person known by name only. A list of subjects, cross-referenced to the specializing activity, is provided for the rapid location of personnel knowledgeable in a particular matter. This listing covers 524 primary subjects, many of which are further suggested.

MHC

P 146119 Plasteo Note 13 UNLIMITED  
 Picatinny Arsenal, Plastics Tech.  
 Evaluation Center, Dover, N.J., U.S.A. 061.3 "6.1966"  
 PLASTICS IN GOVERNMENT: A REPRINTING OF 678.6  
 FOUR CONFERENCE PAPERS, 1966 ANNUAL CONFERENCE,  
 SOCIETY OF THE PLASTICS INDUSTRY  
 (JUNE 7-9, NEW YORK CITY)  
 Pably, H.E.  
 July, 1966 46pp., 7ref.

The papers are:- Plastics in ammunition (Matlack, J.D.); Plastic development in ships (Hifers, J.B.); Applications of plastics for aerospace use (Postolnek, W.); Needs for characterization and process control of low-density composites for aerospace application (Parker, J.L.).

MHC

NSA TT F-10174 N66-28370 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 STUDY OF THE POLYMERIZATION REACTION OF 678.746.52  
 POLYBENZIMIDAZOLES  
 Korshak, V.V., Frunze, T.M., et al.  
 May, 1966 9pp., 4ref.

The mechanism of the synthesis of polybenzimidazoles is investigated on the example of the polycondensation reaction of 3,3'-diaminobenzidine with the diphenyl ester of sebacic acid. Thermographic analyses showed the reaction temperature to be of major significance. An increase led to a sharp rise in molecular weight of the polymer and shortening of the reaction time. During the first stages, the reaction is of the equilibrium kind, accompanied by cessation of chain growth; during later stages, the equilibrium character is lost due to the presence of extremely stable benzimidazole rings in the macromolecules.

PMH

#### METALLURGY

P 146504 FR N&A CR 76061 UNLIMITED  
 N66-29907  
 Ipson Industries Inc., Rockford, Ill., U.S.A. 669-405.8  
 INVESTIGATION OF FOAMED METALS FOR LUNCH AND N&S 8-11048  
 SPACE VEHICLE APPLICATION (29.6.1963-30.11.1965)  
 Byrnes, E.R., Twine, C.J.  
 May, 1966 116pp., 13ref.

Investigations of methods for manufacturing porous metals are reported. Effects of variables in processing and fabrication on the ultimate strength and integrity of foam metals are discussed. The foamed metals studied were aluminum, titanium, nickel, 316 stainless steel, H-11 tool steel, and molybdenum. No unusual difficulties were encountered in preparing foam metals of molybdenum, H-11 tool steel, 316 stainless steel and nickel; however, at densities less than 15% of theoretical, the foam metals exhibited brittle fracture characteristics. Since no practical mechanical or chemical method was discovered to prevent or remove the formation of oxide film around the aluminum metal particles, useable foamed aluminum was not produced.

GMH

S &amp; T Memo 1/67

Technical Information & Library Services,  
Ministry of Aviation, U.K.STRETCH FORMING OF VERY LONG STAINLESS STEEL  
SKINS (Report of work by Hawker Siddelay  
Aviation Ltd., under Ministry of Aviation  
Contract)

Fadley, N., Fray, J.

Feb., 1967 11pp.

Precipitation hardening FV 520 stainless steel was stretch formed in the fully softened (austenitic) and the cold rolled and transformed (martensitic) conditions using the H.S.A. 250t stretching machine; the skins were subjected to various heat treatments after forming. It was shown that FV520 skins up to at least 45 ft long can be stretch formed satisfactorily in the soft condition only. Forming in the harder condition gave rise to considerable springback. Long skins of FV520 could be heat treated satisfactorily after stretch forming, but low temperature transformation was impractical due to problems of distortion.

GHI

UNLIMITED

621.983.7

669.14.018.8

669.146

XB/1/0135/CD.43(a)(2)

P 146192

AR-592-1-365

N66-22934

UNLIMITED

N.E. CR 54614

General Dynamics Corp., Astronautics Div.,  
San Diego, Calif., U.S.A.

669.14.018.85:

539.3.096

THE EFFECTS OF COLD ROLLING ON THE MECHANICAL  
PROPERTIES OF TYPE 310 STAINLESS STEEL AT ROOM  
AND CRYOGENIC TEMPERATURES

Christian, J.L., Gruner, J.D., et al.

27.11.1962 23pp., 16ref.

The purpose of this investigation was to determine the applicability of cold rolled type 310 stainless steel (Cr 25%, Ni 20% approx.) for structural uses at cryogenic temperatures. Yield and tensile strengths, elongation and notched toughness were determined as a function of cold rolling from 0 to 92% reduction and of temperature from 78 deg. to -423 deg.F (26 to -253 deg.C). The results indicate that high strengths may be achieved by cold rolling and that the toughness is adequate for structural applications at -423 deg.F for the 0 - 85% cold rolled tempers. An evaluation was also made of the room temperature formability of annealed and cold rolled 310 stainless steel.

GHI

P 146175

NR0-293

N.E. CR 54747

UNLIMITED

N66-22932

General Dynamics Corp., Convair Div.,  
San Diego, Calif., U.S.A.

669.14.018.85

539.3.096

THE EFFECTS OF COLD ROLLING ON THE NOTCHED AND  
UNNOTCHED TENSILE PROPERTIES OF TYPE 310  
STAINLESS STEEL AT + 75 DEG.F, - 320 DEG.F,  
AND - 423 DEG.F

Gruner, J.D.

2.2.1962 15pp.

The effects of various degrees of cold rolling on the notched and unnotched longitudinal and transverse tensile properties of Type 310 stainless steel sheet (Cr 25%, Ni 20% approx.) were determined at +75, -320 and -423 deg.F (+24, -196 and -253 deg.C). Tests results showed that this material exhibits good notched toughness at cryogenic temperatures. The notch toughness at -320 and -423 deg.F improved with increased cold rolling until a maximum was reached at approximately 60% reduction. Further cold working decreased the low temperature notched toughness.

GHI

AD 639619

SSC-174

FR

UNLIMITED

National Res. Council, Ship Structure  
Committee, Washington, D.C., U.S.A.

669.146:

669.798:

INVESTIGATION OF RESIDUAL STRESSES IN STEEL  
WELDEMENTS

539.319:

621.791:

Matsubuchi, K., Martin, D.C.

539.56:

Sept., 1966 103pp., 26ref.

Nobs 92521

Experimental hydrogen-induced-cracking tests were made on 45 weldments in mild steel HY-80 steel, a commercial high-strength structural steel, and SAE 4340 steel. Extensive cracks were found in weldments made in SAE 4340 steel (oil quenched and tempered at 500 deg.F) after hydrogen charging for relatively short times. Systematic crack patterns that could be related to residual stress distributions were obtained on various complex weldments. When steels of lower strengths were used, longer charging time was required to produce cracks, and crack patterns were less pronounced. The hydrogen-induced-cracking technique does not seem to work on mild-steel weldments.

GHI

P 140461 ER-6373 Intn Engrg Rep.2 UNLIMITED  
 NASA CR 72011  
 N66-33504 669,245  
 T.W. Inc., Equipment Labs., 621,434-253.5  
 Cleveland, Ohio, U.S.A. LB3-7267

TASK 1, CONCLUDING REPORT, DEVELOPMENT OF  
 HIGH TEMPERATURE NICKEL-BASE ALLOYS FOR JET  
 ENGINE TURBINE DUCT APPLICATIONS  
 (1.10.1965 - 31.5.1966)

Collins, H.E.  
 20.6.1966 145pp., 12ref.

A screening study was conducted in which 75 experimental compositions were melted, cast and evaluated on the basis of mechanical property, micro-structure and workability results. From this study, three promising cast and five promising wrought alloys were established and recommended for a more complete property evaluation. The elements most influential in improving stress rupture life were Ti, W, Ni, Al, and Cr. It is stated that these elements, in the percentages suggested, generally increase life and tensile strength, but they normally decreased ductility and workability. The data obtained from these investigations are given, and the alloy candidates recommended for further evaluation are identified. GKH

NASA TT F-10156 UNLIMITED  
 National Aero. & Space Admin., U.S.A.  
 ELECTRON DIFFRACTION STUDY OF THE OXIDATION 669,248,61:  
 PROCESS OF THIN FILMS OF INTERMETALLIC 669,718,61:  
 COMPOUNDS OF THE SYSTEM NICKEL-ALUMINUM 669,715,24:  
 Nazarov, R.I. 669,243,71  
 May, 1965 7pp., 11ref. 621,793,14

A method for preparing intermetallic compounds of the nickel-aluminum system in the form of thin films, by vacuum evaporation and condensation of the metal vapour until the percentage composition of the alloy corresponded to a given point of the phase diagram, is described. Electron diffraction studies were used for determining the heat resistance of the alloys and the structure of the oxide films. Simultaneous deposition of aluminum and nickel from two different evaporators on a liquid-nitrogen cooled base resulted not only in reflections characteristic of the two metals but also in reflections characteristic of the compound NiAl. GKH

NASA TT D-3325 UNLIMITED  
 National Aero & Space Admin., Washington, D.C. U.S.A.  
 CRACK PROPAGATION, DELAYED FAILURE, AND 620,193,27:  
 RESIDUAL STATIC STRENGTH OF TITANIUM, ALUMINUM, 669,295,5171281292:  
 AND STAINLESS STEEL ALLOYS IN AQUEOUS 669,715151721:  
 ENVIRONMENTS 669,715131721  
 Figue, I.E., Hudson, C.M.  
 Feb., 1967 41pp., 11ref.

An investigation of crack propagation, delayed failure, and residual static strength was conducted on titanium, aluminum, and stainless steel alloys in air in a 3% salt solution, and in sea water. Fatigue cracks grew approximately 2 to 3 times faster in the aqueous environment than in air in Ti-6Al-4V (duplex annealed) titanium alloy and 7075-T6 aluminum alloy. In the 2024-T3 aluminum alloy, the aqueous environment had a deleterious effect on the crack growth rate at the lower stress levels and a beneficial effect at the high stress levels. In general, the delayed failure strengths of the aluminum and stainless steel alloys were essentially the same as their residual static strengths in air. GKH

AD 630523 AFM TR 66-19 UNLIMITED  
 Army Materials Res. Agency, Watertown,  
 Mass., U.S.A. 669,715:  
 WETTING AND BONDING BETWEEN ALUMINUM 661,662,22:  
 ALLOYS AND SAPPHIRE 532,696,1  
 Wolf, S.M., Levitt, A.P., et al.  
 July, 1966 12pp., 9ref.

Wetting and bonding between the basal plane of single crystal sapphire and several aluminum alloys were investigated by the sessile drop technique at 1300 and 1600 deg.F (704 and 871 deg.C) in vacuo of  $10^{-4}$  Torr. The alloys were commercially pure (99%) aluminum, commercially pure aluminum with small additions of each of eleven elements, and three commercial aluminum alloys. Additions of zirconium, magnesium, and copper lowered the aluminum-sapphire equilibrium contact angle; the lowest contact angle observed was 94 deg. and was obtained with 0.9% atomic % addition of magnesium to pure aluminum. GKH

P 146508 Summary Rep. N66-23655 UNLIMITED  
 NABA CR 74443  
 Aluminum Co. of America, Alcoa Res. Labs., 620.194.2;  
 New Kensington, Pa., U.S.A. 669.715;  
 INVESTIGATION OF THE STRESS-CORROSION CRACKING 62.791  
 OF HIGH STRENGTH ALUMINUM ALLOYS NAB 8-5340  
 (6.5.1963 - 6.7.1965)  
 Lifka, B.L., King, W., et al.  
 1.8.1965 158pp., 19ref.

Stress corrosion cracking of several high-strength aluminium alloys was tested in various environments, after protective surface treatments and coatings, and after tempering and weldings. Parent Al-Zn-Mg alloys were little affected; but in the as-welded condition, all investigated Al alloys suffered severe localized corrosions of the heat affected zones. Post-weld ageing eliminated this effect greatly. Good stress-corrosion cracking resistance was obtained for all alloys when they were welded and stressed either in bending, or in tension as high as 75% of their weldment strength. Post-weld ageing decreased weld-strength to corrosion cracking markedly.

GMH

P 146470 PR NABA CR 77778 UNLIMITED  
 N66-35982  
 West Virginia Univ., Chemical Engineering Dept., 669.715.018.95;  
 Morgantown, U.S.A. 669.13  
 PRODUCTION OF DISPERSION ALLOYS WITH THE AID OF 534.321.9  
 ULTRASONICS NAB 8-533  
 Fairbanks, H.V.  
 June, 1966 10pp., 3ref.

The results are summarized from research on the dispersion of inerts in a molten matrix by ultrasonic energy, and the ultrasonic treatment of alloys to produce dispersion strengthening. Mixing an inert material into molten aluminium indicated that a nearly uniform dispersion by the use of ultrasonics could be obtained. It is also reported that inoculation during the solidification of gray cast iron produced more ferrite and less pearlite than the non-inoculated reference specimen. Additional results are given and recommendations for further study are made.

GMH

P 146505 D2-20478-1 NABA CR 54837 UNLIMITED  
 N66-19586  
 Boeing Co., Seattle, Wash., U.S.A. 669.715.3;  
 INVESTIGATION OF PLANE-STRAIN FLAW GROWTH IN 669.295.517.16;  
 THICK-WALLED TANKS (26.6.1964 - 26.10.1965) 539.56  
 Tiffany, C.F., Lorenz, P.H., et al. NAB 3-41.94  
 Feb., 1966 16pp., 23ref.

Plane-strain cyclic flaw-growth rates and fracture-toughness values were obtained for 2219-T87 aluminium and 5A1-2.5Sn (ELI) titanium. Investigations were conducted at room temperature, -320 and -423 deg.F (-96 and -253 deg.C) and under zero-to-tension and half-tension-to-tension loading profiles. The experimental approach used linear elastic fracture mechanics. Results from surface-flawed uniaxial specimens and cylindrical tanks were obtained and compared. It was concluded that, within limitations, the uniaxial data can be usefully applied in the design of cryogenic pressure vessels.

GMH

RAE TR 66204 CPH 77 UNLIMITED  
 Royal Aircraft Est., Ministry of Aviation, N.K.  
 A COMPARISON OF THE FATIGUE BEHAVIOUR OF TWO 669.715.517.2  
 ALUMINIUM-ZINC-MAGNESIUM ALLOYS 539.431.4  
 Stubbington, C.A., Forsyth, P.J.E.  
 June, 1966 30pp., 5ref.

The torsional fatigue deformation of two aluminium alloys, Al-7.5Zn-2.5Mg and Al-4Zn-5Mg, has been examined in various conditions of heat treatment. Two well defined deformation modes were observed, one in which localised transcrystalline slip produced narrow zones of precipitate re-solution, and another in which localised deformation occurred in the precipitate depleted zones at the grain boundaries. An attempt was made to correlate the torsional deformation modes of the two alloys with the fracture modes observed on rotating bending corrosion fatigue test pieces.

GMH

P 146172 FR NASA CR 7731 UNLIMITED  
 186-3577  
 Southwest Res. Inst., San Antonio, U.S.A.  
 DEVELOPMENT OF WELDING TECHNIQUES AND FILLER  
 METALS FOR HIGH STRENGTH ALUMINUM ALLOYS  
 Burghard, H.C., Norris, E.B.  
 27.5.1966 269pp., 25ref.

669.716:  
 621.791.75  
 NAS8-1529  
 NAS8-20160

Possible means of improving the strength of welded aluminum alloys were investigated, and the mechanical and metallurgical characteristics of these types of weldments were better defined. The programme included: (1) development of welding techniques and filler metal alloys, and (2) evaluation of the uniaxial and biaxial mechanical properties of aluminum alloy weldments. Metal inert gas, and tungsten inert gas weldments of various aluminum alloys were studied. It was established that joint preparation methods (machining, cleaning, etc.) exert a strong influence on the soundness of the welds for all material process combination included in the study.

GHR

AD 640137 NAEC ANL 2478 UNLIMITED  
 Naval Air Engineering Center, Aeronautical  
 Materials Lab., Philadelphia, Pa., U.S.A.  
 A RADIOCHEMICAL INVESTIGATION OF THE LEACHING  
 OF CHROMIUM FROM CHEMICALLY CHROMATED ALUMINUM  
 SURFACES

669.716.9:  
 621.794.6

Glass, A.L.  
 19.7.1966 23pp., 6ref.

A reproducible and accurate radioactive tracer procedure using the isotope chromium-51 has been developed to measure the "leaching" rates, in situ, of chromium from chemically chromated aluminum surfaces. Studies of the rates of solution are reported and an interpretation of these results is presented.

GHR

P 146143 Special Rep. NASA CR 74034 UNLIMITED  
 N66-23505  
 Battelle Memorial Inst., Columbus Labs.,  
 Ohio, U.S.A.  
 REVIEW OF LITERATURE ON HYDROGEN EMBRITTLEMENT  
 Groeneveld, T.P., Fletcher, E.E., et al.  
 12.1.1966 75pp., 98ref.

539.56:  
 669.788  
 NAS 8-20029

Deals primarily with the loss in mechanical properties experienced by high strength iron-base and nickel-base alloys and by titanium as a result of hydrogen introduced into the material during manufacturing and processing of the alloy, or in service. The programme was conducted to determine the susceptibility of specified materials to hydrogen stress cracking, with particular attention being given to the susceptibility to hydrogen stress cracking induced by various commonly used cleaning, pickling, and electroplating processes, and to determine the effectiveness of various hydrogen embrittlement relief treatments.

GHR

#### MISCELLANEOUS

UKSH Rep.66/76

OPEN DISTRIBUTION  
 UNLIMITED

U.K. Scientific Mission, Washington, D.C., U.S.A.  
 NOTES ON A SYMPOSIUM OF TECHNOLOGY AND WORLD TRADE  
 SPONSORED BY THE SECRETARY OF COMMERCE OF THE  
 UNITED STATES: NATIONAL BUREAU OF STANDARDS,  
 GAITHERSBURG, MARYLAND, NOVEMBER 16-17, 1966  
 Voysey, R.D.  
 Dec., 1966 16pp.

061.3 "11.1966"  
 389.6:  
 382

The symposium, besides presenting a plea for more extensive standardization and a little material on world trade, gave some recent findings on the problem of stimulating technology and innovation. The scrutiny of this problem has grown steadily in the U.S., particularly in this decade, because of its obvious importance for sustained economic growth at a time when American policy commitments, external and internal, continue to grow and there is some disappointment at signs of slackening of the rate of growth of technological and trade achievement.

LBT



AD 640619 P-3462 UNLIMITED  
 Rand Corp., Santa Monica, Calif., U.S.A.  
 REVIEW OF "THE POLITICS OF THE CHINESE RED ARMY" 355J(210)  
 EDITED BY CHESTER CHENG, THE HOOVER INSTITUTE,  
 1966

Hsieh, A.L.

Aug., 1966

3pp.

"The Politics of the Chinese Red Army" is a volume of some 800 pages, containing a translation of 29 issues of a secret military journal covering the period 1 Jan. to 26 Aug. 1964. The reviewer considers that it is a very valuable contribution to Western knowledge of communist China, but points out some mistranslations.

LBT

P 146432 Monograph 13 UNLIMITED  
 Bureau of Mines, Washington, D.C., U.S.A.  
 OIL RECOVERY FROM GAS-CAP RESERVOIRS: 622.323  
 AN ENGINEERING EVALUATION OF CONSERVATION PRACTICES 622.276.23  
 IN SIX RESERVOIRS

Weaver, L.K., Anderson, K.E.

1966

106pp., 17ref.

This report describes the performance of six gas-cap reservoirs that are examples of both good engineering and good regulatory practices. Operations presented show: (1) water injection at the gas-oil contact to isolate the gas cap and maintain the reservoir pressure, (2) return gas produced with the oil to the gas cap while using the recovery mechanism of gravity drainage and natural-water influx to produce the oil zone, (3) cycling the gas-cap supplemented with extraneous gas to maintain the reservoir pressure while utilizing the natural water influx to produce the oil zone; the condensate is recovered with minimum retrograde losses, (4) in the early stages of production, injecting water below the water-oil contact (continued)

P 146432 (continued)

to maintain the reservoir pressure to prevent excessive gas-cap expansion and retrograde condensation; in the latter stages of production the gas-cap gas is cycled to recover the condensate without retrograde losses, (5) initially returning gas produced with the oil to the cap and simultaneously injecting water below the water-oil contact to prevent movement of the gas-oil contact and maintain reservoir pressure, and (6) controlling withdrawals from the gas cap and the oil zone and not using pressure maintenance.

PAH

UKSM Rep. 67/8

OPEN DISTRIBUTION  
 UNLIMITED

U.K. Scientific Mission, Washington, D.C., U.S.A.  
 THE ADVANCED WASTE TREATMENT RESEARCH PROGRAMME  
 Griffiths, D.L.

Jan., 1967

5pp.

628.34  
 661.63.2  
 66.064

This report covers visits to the Robert A. Taft Sanitary Engineering Centre, Cincinnati and the Lebanon Pilot Plant Facility, Lebanon, Ohio. Themes described include (a) Lebanon sewage effluent (b) the activated carbon adsorption method (c) electrodialysis in waste water renovation (d) Pretreatment in the electrodialysis system etc., etc.

PAH